

MATERIAL SAFETY DATA SHEET (MSDS)**BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)****1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)

Product code : B0044800100

Identification of the product : BISMUTH SUBNITRATE 71%
CAS No :10361-46-3**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet**Company identification**SUVCHEM
Chaitanya Tower, 2nd Floor, Office # 206,
Siddharth Nagar, S.V. Road,
Goregaon (West), Mumbai - 400062,
Maharashtra, India.
Contact: +91 22 28725393 / 94 / 95
Email ID: info@suvchem.com/care@suvchem.com**1.4. Emergency telephone number**

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]

2. Hazards identification -DSD**2.1. Classification of the substance or mixture****Classification EC 67/548 or EC 1999/45**

Classification : Xi; R36

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)Health hazards : Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation -
Category 3 - Warning (CLP : STOT SE 3) H335
Eye irritation - Category 2A - Warning (CLP : Eye Irrit. 2) H319
Skin irritation - Category 2 - Warning (CLP : Skin Corr. 2) H315**2.2. Label elements****Labelling EC 67/548 or EC 1999/45**

MATERIAL SAFETY DATA SHEET (MSDS)
BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)
2. Hazards identification -DSD (continued)

Symbol(s)



Symbol(s)

: O : Oxidizing
Xi : Irritant

R Phrase(s)

:
R36 : Irritating to eyes.
R37 : Irritating to respiratory system.
R38 : Irritating to skin.

S Phrase(s)

: S17 : Keep away from combustible material.
S26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36 : Wear suitable protective clothing.
S37 : Wear suitable gloves.
S39 : Wear eye/face protection.
Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms



Signal words

: Warning

Hazard statements

: H319 : Causes serious eye irritation.
H315 : Causes skin irritation.
H335 : May cause respiratory irritation.

Precautionary statements

• Prevention

: P280: Wear protective gloves, protective clothing, eye protection, face protection.
P271: Use only outdoors or in a well-ventilated area.
P261: Avoid breathing dust, fume, gas, mist, vapours, spray.
P264: Wash thoroughly after handling.

• Response

: P302+P352: IF ON SKIN : Wash with plenty of soap and water.
P332+P313: If skin irritation occurs : Get medical advice.
P305+P351+P338: IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing.
P363: Wash contaminated clothing before reuse.

• Storage

: P403+P233: Store in well-ventilated place. Keep container tightly closed.
P405: Store locked up.

• Disposal considerations

: P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

MATERIAL SAFETY DATA SHEET (MSDS)

BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)

2. Hazards identification -DSD (continued)

Other hazards : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

Substance / Preparation : BISMUTH SUBNITRATE 71%
CAS No :10361-46-3
Substance.

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures

4.1. Description of first aid measures

Inhalation : Call a POISON CENTER or doctor if you feel unwell. Remove to fresh air and keep at rest in a position comfortable for breathing.

Skin contact : Specific treatment (see on this label). Get medical advice. If skin irritation occurs : Wash with plenty of soap and water. Wash contaminated clothing before reuse.

Eye contact : If eye irritation persists : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Get medical advice.

Ingestion : Obtain emergency medical attention. Do NOT induce vomiting. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use : Causes serious eye irritation.
Causes skin irritation. May cause respiratory irritation.

4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

Surrounding fires : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

MATERIAL SAFETY DATA SHEET (MSDS)

BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)

5. Fire-fighting measures (continued)

Hazardous combustion products : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Special procedures : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection. Ventilate area.

For non-emergency personnel : Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods : On land, sweep or shovel into suitable containers. Minimize generation of dust. Store away from other materials.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling

Handling : Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wash thoroughly after handling.

Technical protective measures : Provide good ventilation in process area to prevent formation of vapour.

Special precautions : Avoid breathing dust, fume, gas, mist, vapours, spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep only in the original container in a cool, well ventilated place. Keep container tightly closed.

MATERIAL SAFETY DATA SHEET (MSDS)
BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)
7. Handling and storage (continued)

Storage - away from : Strong bases. Strong acids. Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Specific end use(s) : None.

8. Exposure controls/personal protection
8.1. Exposure controls
Personal protection


Personal protection : Avoid all unnecessary exposure.

- **Respiratory protection** : Wear approved mask.
- **Hand protection** : Wear protective gloves.
- **Skin protection** : Wear suitable protective clothing.
- **Eye protection** : Chemical goggles or safety glasses.
- **Others** : When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits : No data available.

9. Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state at 20 °C : Solid.

Colour : White powder

Odour : Odorless

Odour threshold : No data available.

pH value : Not applicable.

Melting point [°C] : 500 °C

Decomposition point [°C] : N/A

Critical temperature [°C] : N/A

Auto-ignition temperature [°C] : N/A

Flammability (solid, gas) : N/A

Flash point [°C] : N/A

MATERIAL SAFETY DATA SHEET (MSDS)
BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)
9. Physical and chemical properties (continued)

Boiling point [°C]	: N/A
Initial boiling point [°C]	: N/A
Final boiling point [°C]	: N/A
Evaporation rate	: N/A
Vapour pressure [20°C]	: N/A
Vapour pressure mm/Hg	: N/A
Vapour density	: N/A
Density [g/cm ³]	: 4,928
Relative density, gas (air=1)	: N/A
Relative density, liquid (water=1)	: N/A
Solubility in water [% weight]	: Insoluble in water
Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: N/A
Viscosity at 40°C [mm ² /s]	: N/A

9.2. Other information

Explosive properties	: N/A
Explosion limits - upper [%]	: N/A
Explosion limits - lower [%]	: N/A
Oxidising properties	: No data available.

10. Stability and reactivity
10.1. Reactivity

Reactivity	: Not established.
------------	--------------------

10.2. Chemical stability

Chemical stability	: Stable under recommended storage conditions.
--------------------	--

10.3. Possibility of hazardous reactions

Hazardous reactions	: Not established.
---------------------	--------------------

10.4. Conditions to avoid

Conditions to avoid	: Direct sunlight. Extremely high or low temperatures.
---------------------	--

10.5. Incompatible materials

MATERIAL SAFETY DATA SHEET (MSDS)
BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)
10. Stability and reactivity (continued)

Materials to avoid : Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products : Fumes. Carbon monoxide. Carbon dioxide.

11. Toxicological information
11.1. Information on toxicological effects
Acute toxicity

- **Inhalation** : Based on available data, the classification criteria are not met.
- **Dermal** : Based on available data, the classification criteria are not met.
- **Ingestion** : Based on available data, the classification criteria are not met.

Corrosion : Based on available data, the classification criteria are not met.

Irritation : Causes serious eye irritation.
 Causes skin irritation.
 May cause respiratory irritation.

Sensitization : Based on available data, the classification criteria are not met.

Mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Toxic for reproduction : Based on available data, the classification criteria are not met.

STOT-single exposure : Based on available data, the classification criteria are not met.

STOT-repeated exposure : Based on available data, the classification criteria are not met.

Aspiration hazard : Based on available data, the classification criteria are not met.

12. Ecological information
12.1. Toxicity

Toxicity information : Not established.

12.2. Persistence - degradability

Persistence - degradability : Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential : Not established.

12.4. Mobility in soil

MATERIAL SAFETY DATA SHEET (MSDS)

BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)

12. Ecological information (continued)

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions : Avoid release to the environment.

13. Disposal considerations

13.1. Waste treatment methods

General : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.

14. Transport information

14.1. Land transport (ADR-RID)

Proper shipping name : NITRATES, INORGANIC, N.O.S.
UN N° : 1477
H.I. nr : 50
ADR - Class : 5.1
Labelling - Transport : 5.1 : Oxidizing substances.



ADR - Classification code : O2
O2
ADR - Group : II
ADR - Packing instructions : P002
ADR - Limited Quantity : 1 KG
ADR - Tunnel code



MATERIAL SAFETY DATA SHEET (MSDS)

BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)

14. Transport information (continued)

: E : Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name : NITRATES, INORGANIC, N.O.S.
UN N° : 1477
IMO-IMDG - Class or division : 5.1 : Oxidizing substances.
IMO-IMDG - Packing group : II
IMO-IMDG - Packing instructions : P002
IMO-IMDG - Limited quantities : 1 kg
IMO-IMDG - Marine pollution : Yes
EMS-Nr : F-A S-Q

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name : NITRATES, INORGANIC, N.O.S.
UN N° : 1477
IATA - Class or division : 5.1 : Oxidizing substances.
IATA - Packing group : II
IATA - Passenger and Cargo Aircraft : ALLOWED
- Passenger and Cargo - Packing instruction : 558
- Passenger and Cargo - Maximum Quantity/Packing : 5 kg
IATA - Cargo only : ALLOWED
- Cargo only - Packing instruction : 562
- Cargo only - Maximum Quantity/Packing : 25 kg
IATA - Limited Quantities : 2.5 kg
ERG-Nr : 5L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental regulations/legislation specific for the substance or mixture : Ensure all national/local regulations are observed.
REACH Restrictions - Annex XVII : The components of this product are not subject to restrictions.
REACH Authorisation - Annex XIV : The components of this product are not subject to authorization.

15.2. Chemical Safety Assessment

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

BISMUTH SUB NITRATE LR (BISMUTH OXYNITRATE)

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document