

CHAITANYA CH5, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

DI-LITIHUM TETRABORATE AR

1. Product Identification

Synonyms: Lithium Borate; Dilithium Salt; Boron Lithium Oxide CAS No.: 12007-60-2

Product Coad: L0122105000

Molecular Weight: 169.11 Chemical Formula: Li2B4O7

2. Composition/Information on Ingredients

Ingredient	CAS No	Perce	ent	Hazard	ous
Boric Acid, Dilithium Salt	12007	-60-2	99 - 10	00%	Yes

3. Hazards Identification

Emergency Overview

WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM, RESPIRATORY SYSTEM, MUSCLES AND KIDNEYS.

Inhalation: Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. Inhalation may result in symptoms and problems similar to ingestion.

Ingestion: Causes irritation to the gastrointestinal tract. Symptoms may include nausea, vomiting and diarrhea. In severe cases, lithium can cause apathy, sluggishness, drowsiness, slurred speech, blurred vision, irregular eye movements, weakness, incoordination, lethargy, heart effects, brain effects, ringing in the ears, tremors and muscle twitching, central nervous system damage, kidney effects, thyroid changes, coma, pulmonary edema, and renal failure.

Skin Contact: Causes irritation to skin. Symptoms include redness, itching, and pain. May be absorbed through damaged or burned skin with symptoms similar to inhalation and ingestion.

Eye Contact: Causes irritation, redness, and pain.

Chronic Exposure: Repeated exposure may cause symptoms similar to those listed for acute effects.

Aggravation of Pre-existing Conditions: Persons with pre-existing skin, eye, blood or central nervous system disorders, or impaired liver, kidney, or pulmonary function may be more susceptible to the effects of this substance.

4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard.

Explosion: Not considered to be an explosion hazard.

Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire.

Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

DI-LITIHUM TETRABORATE AR

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: None established.

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. Personal Respirators (NIOSH Approved): For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH type N95 or better filters) may be worn. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-face positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Eye Protection: Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: White Powder. Odor: Odorless. Solubility: Moderate (1-10%) Specific Gravity: 2.4 g/cc at (70F) pH: No information found. % Volatiles by volume @ 21C (70F): 0 Boiling Point: No information found. Melting Point: 917C (1683F) Vapor Density (Air=1): Not applicable. Vapor Pressure (mm Hg): Not applicable. Evaporation Rate (BuAc=1): No information found.

10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.
Hazardous Decomposition Products: May produce oxides of lithium, boron, and carbon.
Hazardous Polymerization: Will not occur.
Incompatibilities: Strong acids.
Conditions to Avoid: Incompatibles.

11. Toxicological Information

No LD50/LC50 information found relating to normal routes of occupational exposure.

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category

Boric Acid, Dilithium Salt No No None

(12007-60-2)

12. Ecological Information

Environmental Fate: No information found. Environmental Toxicity: No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Not regulated.



CHAITANYA CH5, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

DI-LITIHUM TETRABORATE AR

15. Regulatory Information

\Chemical Inventory Status - Part 1\				
Ingredient	TSCA EC Japan Australia			
Boric Acid, Dilithium Salt (12007-	60-2) Yes Yes Yes Yes			
\Chemical Inventory Status - Part 2\				
	Canada			
Ingredient	Korea DSL NDSL Phil.			
Boric Acid, Dilithium Salt (12007-60-2) Yes Yes No Yes				
\Federal, State & International Regulations - Part 1\				
-SARA	302SARA 313			
Ingredient RC	Q TPQ List Chemical Catg.			
Boric Acid, Dilithium Salt (12007-60-2) No No No No				
\Federal, State & International Regulations - Part 2\				
	-RCRATSCA-			
Ingredient CE	RCLA 261.33 8(d)			
Boric Acid, Dilithium Salt (12007-	60-2) No No No			
Chemical Weapons Convention: No TSCA 12(b): No CDTA: No				
SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No				
Reactivity: No (Pure / Solid)				

Australian Hazchem Code: None allocated.

Poison Schedule: None allocated.

WHMIS: This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 2 Flammability: 0 Reactivity: 0 Label Hazard Warning: WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM, RESPIRATORY SYSTEM, MUSCLES AND KIDNEYS. Label Precautions: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing dust.

Keep container closed. Use only with adequate ventilation.

Label First Aid:

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with



CHAITANYA CH5, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

DI-LITIHUM TETRABORATE AR

plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention.

Product Use: Laboratory Reagent.

In accordance with REACH Regulation (CE) Nº 1907/2006 and with CLP Regulation (CE) Nº 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document