

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
Trade name	: MERCURIC ACETATE LR	
Product code Identification of the product	: M0133100100 : MERCURIC ACETATE EXTRA PURE 98.5% CAS No: 1600-27-7	
1.2. Relevant identified uses of the substance or mixture and uses advised against		
Use	: Industrial. For professional use only.	
1.3. Details of the supplier of the safety data sheet		
Company identification	SUVCHEM Chaitanya Tower, 2nd Floor, Office # 206, Siddharth Nagar, S.V. Road, Goregaon (West), Mumbai - 400062, Maharashtra, India. Contact: +91 22 28725393 / 94 / 95 Email ID: info@suvchem.com/care@suvchem.com	
1.4. Emergency telephone number		
Phone no.	: + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]	

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification	: T+; R26/27/28
	R33
	N: R50-53

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards	: Acute toxicity, dermal - Category 1 - Danger (CLP : Acute Tox. 1) H310 Acute toxicity, Inhalation - Category 2 - Danger (CLP : Acute Tox. 2) H330 Acute toxicity, Oral - Category 1 - Danger (CLP : Acute Tox. 1) H300
Environmental hazards	: Hazardous to the aquatic environment - Acute hazard - Category 1 - Warning (CLP : Aquatic Acute 1) H400 Hazardous to the aquatic environment - Chronic hazard - Category 1 - Warning (CLP : Aquatic Chronic 1) H410

2.2. Label elements



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

2. Hazards identification -DSD (continued)

Labelling EC 67/548 or EC 1999/45

Symbol(s)



Symbol(s)	: T+ : Very toxic N : Dangerous for the environment	
R Phrase(s)	: R26/27/28 : Very toxic by inhalation, in contact with skin and if swallowed. R33 : Danger of cumulative effects. R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
S Phrase(s)	 S13 : Keep away from food, drink and animal feedingstuffs. S28 : After contact with skin, wash immediately with S36 : Wear suitable protective clothing. S45 : In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible). S60 : This material and its container must be disposed of as hazardous waste. S61 : Avoid release to the environment. Refer to special instructions/Safety data sheets. 	
Labelling Regulation EC 1272/2008 (CLP)		
Hazard pictograms		

	\vee \vee \vee
Signal words	: Danger
Hazard statements	 : H300 : Fatal if swallowed. H310 : Fatal in contact with skin. H330 : Fatal if inhaled. H410 : Very toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	 P284: Wear respiratory protection. P280: Wear protective gloves, protective clothing, eye protection, face protection. P271: Use only outdoors or in a well-ventilated area. P260: Do not breathe dust, fume, gas, mist, vapours, spray. P273: Avoid release to the environment. P264: Wash thoroughly after handling. P270: Do not eat, drink or smoke when using this product.
• Response	 P301+P310: IF SWALLOWED : Immediately call a POISON CENTER or doctor. P391: Collect spillage. P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing. P302+P350: IF ON SKIN : Gently wash with plenty of soap and water. P363: Wash contaminated clothing before reuse. P361: Remove immediately all contaminated clothing.



MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

2. Hazards identification -DSD (continued)	
• Storage	: P403+P233: Store in well-ventilated place. Keep container tightly closed. P405: Store locked up.
 Disposal considerations 	: P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
2.3. Other hazards	
Other hazards	: The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.
3. Composition/information on ing	gredients
Substance / Preparation	: MERCURIC ACETATE EXTRA PURE 98.5%
Contains no other components or im	Substance. purities which will influence the classification of the product.
4. First aid measures	
4.1. Description of first aid measur	res
Inhalation	: Assure fresh air breathing. Allow the victim to rest. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor. Specific treatment is urgent (see on this label).
Skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Immediately call a POISON CENTER or doctor. Specific treatment (see on this label). Wash with plenty of soap and water. Wash contaminated clothing before reuse. Remove/Take off immediately all contaminated clothing.
Eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
Ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. Specific treatment (see on this label).
4.2. Most important symptoms and effects, both acute and delayed	
Symptoms relating to use	: Fatal if swallowed. Fatal in contact with skin. Fatal if inhaled.
4.3. Indication of any immediate medical attention and special treatment needed	
General information	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

5. Fire-fighting measures

5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media Surrounding fires	: Foam. Dry powder. Carbon dioxide. Water spray. Sand. : Do not use a heavy water stream. : Use water spray or fog for cooling exposed containers.	
5.2. Special hazards arising from the substance or mixture		
Hazardous combustion products	: Under fire conditions, hazardous fumes will be present.	
5.3. Advice for fire-fighters		
Protection against fire	: Do not enter fire area without proper protective equipment, including respiratory protection.	
Special procedures	: Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.	

6.1. Personal precautions, protective equipment and emergency procedures		
For emergency responders	: Equip cleanup crew with proper protection. Ventilate area.	
For non-emergency personnel	: Evacuate unnecessary personnel.	
6.2. Environmental precautions		
Environmental precautions	: Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Avoid release to the environment.	
6.3. Methods and material for containment and cleaning up		
Clean up methods	: On land, sweep or shovel into suitable containers. Minimize generation of dust. Store away from other materials.	
6.4. Reference to other sections		

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

7. Handling and storage (continue	ed)
Handling	: Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust, fume, gas, mist, vapours, spray.
Technical protective measures	: Provide good ventilation in process area to prevent formation of vapour.
7.2. Conditions for safe storage, including any incompatibilities	
Storage	: Keep only in the original container in a cool, well ventilated place. Keep container tightly closed.
Storage - away from	: Strong bases. Strong acids. Sources of ignition. Direct sunlight.
<u>7.3. Specific end use(s)</u>	
Specific end use(s)	: None.
8. Exposure controls/personal protection	
8.1. Exposure controls	
Personal protection	: Avoid all unnecessary exposure.
 Respiratory protection 	: Wear respiratory protection.
 Hand protection 	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Others	: When using, do not eat, drink or smoke.
8.2. Control parameters	
Occupational Exposure Limits	: No data available.
9. Physical and chemical properties	
9.1. Information on basic physical and chemical properties	
Physical state at 20 °C	: Solid.
Colour	: White powder
Odour	: Slight acetic acid odor

Colour	: White powder
Odour	: Slight acetic acid odor
Odour threshold	: No data available.
pH value	: Not applicable.
Melting point [°C]	: 179 - 182 °C
Decomposition point [°C]	: N/A
Critical temperature [°C]	: N/A



MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

9. Physical and chemical properties (continued)

Auto-ignition temperature [°C]	: N/A
Flammability (solid, gas)	: N/A
Flash point [°C]	: N/A
Boiling point [°C]	: N/A
Initial boiling point [°C]	: N/A
Final boiling point [°C]	: N/A
Evaporation rate	: N/A
Vapour pressure [20°C]	: N/A
Vapour pressure mm/Hg	: N/A
Vapour density	: 11
Density [g/cm3]	: 3,27
Relative density, gas (air=1)	: N/A
Relative density, liquid (water=1)	: N/A
Solubility in water [% weight]	: 25 g/100 ml water @
Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: N/A
Viscosity at 40°C [mm2/s]	: N/A
9.2. Other information	
Explosive properties	: N/A
Explosion limits - upper [%]	: N/A
Explosion limits - lower [%]	: N/A
Oxidising properties	: No data available.

10. Stability and reactivity

10.1. Reactivity		
Reactivity	: Not established.	
10.2. Chemical stability		
Chemical stability	: Stable under recommended storage conditions.	
10.3. Possibility of hazardous reactions		
Hazardous reactions	: Not established.	
10.4. Conditions to avoid		



MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

10. Stability and reactivity (continued)			
Conditions to avoid	: Direct sunlight. Extremely high or low temperatures.		
10.5. Incompatible materials			
Materials to avoid	: Strong acids. Strong bases.		
10.6. Hazardous decomposition produced	10.6. Hazardous decomposition products		
Hazardous decomposition products	: Fumes. Carbon monoxide. Carbon dioxide.		
11. Toxicological information			
11.1. Information on toxicological effects			
Acute toxicity			
Inhalation	: Fatal if inhaled.		
• Dermal	: Fatal in contact with skin.		
Ingestion	: Fatal if swallowed.		
Corrosion	: Based on available data, the classification criteria are not met.		
Irritation	: Based on available data, the classification criteria are not met.		
Sensitization	: Based on available data, the classification criteria are not met.		
Mutagenicity	: Based on available data, the classification criteria are not met.		
Carcinogenicity	: Based on available data, the classification criteria are not met.		
Toxic for reproduction	: Based on available data, the classification criteria are not met.		
STOT-single exposure	: Based on available data, the classification criteria are not met.		
STOT-repeated exposure	: Based on available data, the classification criteria are not met.		
Aspiration hazard	: Based on available data, the classification criteria are not met.		
12. Ecological information			
<u>12.1. Toxicity</u>			
Toxicity information	: Very toxic to aquatic life with long lasting effects.		

Persistence - degradability	: May cause long-term adverse effects in the environment.
Persistence - degradability	: May cause long-term adverse effects in the environme

12.3. Bioaccumulative potential

12.2. Persistence - degradability

Bioaccumulative potential : Not established.



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

12. Ecological information (continued)		
<u>12.4. Mobility in soil</u>		
Mobility in soil	: Not established.	
12.5. Results of PBT and vPvB assessment		
Results of PBT and vPvB assess	ment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.	
12.6. Other adverse effects		
Environmental precautions	: Avoid release to the environment.	
13. Disposal considerations		
13.1. Waste treatment methods		
General	 Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. 	
Special precautions	: Hazardous waste due to toxicity.	
14. Transport information		

I/	
Proper shipping name	: MERCURY ACETATE
UN N°	: 1629
H.I. nr	: 60
ADR - Class	: 6.1
Labelling - Transport	: 6.1 : Toxic substances.
	×
ADR - Classification code	: T5
ADR - Group	: 11
ADR - Packing instructions	: P002
ADR - Limited Quantity	: 500 G

14.1. Land transport (ADR-RID)



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

14. Transport information (continued)

ADR - Tunnel code

: D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.



14.2. Sea transport (IMDG) [English only]

Proper shipping name	: MERCURY ACETATE
UN N°	: 1629
IMO-IMDG - Class or division	: 6.1 : Toxic substances.
IMO-IMDG - Packing group	: 11
IMO- IMDG - Packing instructions	: P002
IMO-IMDG - Limited quantities	: 500 g
IMO-IMDG - Marine pollution	: Yes
EMS-Nr	: F-A S-A

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name	: MERCURY ACETATE
UN N°	: 1629
IATA - Class or division	: 6.1 : Toxic substances.
IATA - Packing group	: 11
IATA - Passenger and Cargo Aircraft	: ALLOWED
- Passenger and Cargo - Packing instruction	: 669
- Passenger and Cargo - Maximum Quantity/Packing	: 25 kg
IATA - Cargo only	: ALLOWED
- Cargo only - Packing instruction	: 676
- Cargo only - Maximum Quantity/ Packing	: 100 kg
IATA - Limited Quantites	: 1 kg
ERG-Nr	: 6L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental : Ensure all national/local regulations are observed. regulations/legislation specific for the substance or mixture



MATERIAL SAFETY DATA SHEET (MSDS)

MERCURIC ACETATE LR

In accordance with REACH Regulation (CE) Nº 1907/2006 and with CLP Regulation (CE) Nº 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its
 comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of
 the material by a properly trained person using this product.

End of document

Page :10

AN ISO 9001: 2015 CERTIFIED