

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : NICKEL METAL POWDER (APP. 300 MESH)

Product code : N0142900500

Identification of the product : Nickel
CAS No: 7440-02-0
EC No :231-111-4
Annex No :028-002-00-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification SUVCHEM
Chaitanya Tower, 2nd Floor, Office # 206,
Siddharth Nagar, S.V. Road,
Goregaon (West), Mumbai - 400062,
Maharashtra, India.
Contact: +91 22 28725393 / 94 / 95
Email ID: info@suvchem.com/care@suvchem.com

1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification : Carc. Cat. 3; R40
T; R48/23
R43
R52-53

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Carcinogenicity - Category 2 - Warning (CLP : Carc. 2) H351
Specific Target Organ Toxicity - Repeated exposure - Category 1 - Danger (CLP :
STOT RE 1) H372
Skin sensitisation - Category 1 - Warning (CLP : Skin Sens. 1) H317

Environmental hazards : Hazardous to the aquatic environment - Chronic hazard - Category 3 (CLP :
Aquatic Chronic 3) H412

MATERIAL SAFETY DATA SHEET (MSDS)
NICKEL METAL POWDER (APP. 300 MESH)
2. Hazards identification -DSD (continued)
2.2. Label elements
Labelling EC 67/548 or EC 1999/45
Symbol(s)

Symbol(s)

: Xn : Harmful

R Phrase(s)

: R40 : Limited evidence of a carcinogenic effect.

R43 : May cause sensitization by skin contact.

R48/23 : Toxic : danger of serious damage to health by prolonged exposure through inhalation.

R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S Phrase(s)

: S36/37/39 : Wear suitable protective clothing, gloves and eye/face protection.

S45 : In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible).

S61 : Avoid release to the environment. Refer to special instructions/Safety data sheets.

Contains

: Nickel

Labelling Regulation EC 1272/2008 (CLP)
Hazard pictograms

Signal words

: Danger

Hazard statements

: H351 : Suspected of causing cancer.

H317 : May cause an allergic skin reaction.

H372 : Causes damage to organs through prolonged or repeated exposure.

H412 : Harmful to aquatic life with long lasting effects.

Precautionary statements
• General

: P102: Keep out of reach of children.

P103: Read label before use.

P101: If medical advice is needed, have product container or label at hand.

P201: Obtain special instructions before use.

• Prevention

: P280: Wear protective gloves, protective clothing, eye protection, face protection.

P260: Do not breathe dust, fume, gas, mist, vapours, spray.

P273: Avoid release to the environment.

P264: Wash thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P272: Contaminated work clothing should not be allowed out of the workplace.

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

2. Hazards identification -DSD (continued)

- **Response** : P302+P352: IF ON SKIN : Wash with plenty of soap and water.
P308+P313: If exposed or concerned : get medical advice.
P333+P313: If skin irritation or rash occurs : Get medical advice.
P363: Wash contaminated clothing before reuse.
P314: Get medical advice if you feel unwell.
- **Storage** : P405: Store locked up.
- **Disposal considerations** : P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- Contains** : Nickel

2.3. Other hazards

- Other hazards** : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

Substance / Preparation : Nickel

EC No :231-111-4
Annex No :028-002-00-7
Substance.

Substance name	Contents	CAS No	EC No	Annex No	REACH Ref.	Classification
Nickel	100 %	7440-02-0	231-111-4	028-002-00-7	---	Carc. Cat. 3; R40 T; R48/23 R43 R52-53 STOT RE 1 _ H372 Carc. 2 _ H351 Skin Sens. 1 _ H317 Aquatic Chronic 3 _ H412

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures

4.1. Description of first aid measures

- Inhalation** : Assure fresh air breathing. Allow the victim to rest.
- Skin contact** : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs : Get medical advice. Specific treatment (see on this label).
- Eye contact** : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- Ingestion** : Obtain emergency medical attention. Do NOT induce vomiting. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

4. First aid measures (continued)

Symptoms relating to use : Suspected of causing cancer.
 Causes damage to organs through prolonged or repeated exposure.
 May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.
Surrounding fires : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory protection.
Special procedures : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection.
 Ventilate area.
For non-emergency personnel : Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.
 Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

6. Accidental release measures (continued)

Clean up methods : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Store away from other materials. Collect spillage.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling

Handling : Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust, fume, gas, mist, vapours, spray. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Obtain special instructions before use.

Technical protective measures : Provide good ventilation in process area to prevent formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep only in the original container in a cool, well ventilated place. Keep container closed when not in use.

Storage - away from : Strong bases. Strong acids. Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Specific end use(s) : None.

8. Exposure controls/personal protection

8.1. Exposure controls

Personal protection : Avoid all unnecessary exposure.

- **Respiratory protection** : Wear approved mask.
- **Hand protection** : Wear protective gloves.
- **Eye protection** : Chemical goggles or safety glasses.
- **Others** : When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits : No data available.

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state at 20 °C	: Solid.
Colour	: Greyish black powder
Odour	: Odorless
Odour threshold	: No data available.
pH value	: No data available.
Melting point [°C]	: 1455°C
Decomposition point [°C]	: N/A
Critical temperature [°C]	: N/A
Auto-ignition temperature [°C]	: 87 °C
Flammability (solid, gas)	: N/A
Flash point [°C]	: N/A
Boiling point [°C]	: 2730°C
Initial boiling point [°C]	: N/A
Final boiling point [°C]	: N/A
Evaporation rate	: N/A
Vapour pressure [20°C]	: N/A
Vapour pressure mm/Hg	: N/A
Vapour density	: N/A
Density [g/cm ³]	: 8,098
Relative density, gas (air=1)	: N/A
Relative density, liquid (water=1)	: N/A
Solubility in water [% weight]	: Insoluble in water
Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: 9 - 11 at 20 °C
Viscosity at 40°C [mm ² /s]	: N/A

9.2. Other information

Explosive properties	: N/A
Explosion limits - upper [%]	: N/A
Explosion limits - lower [%]	: N/A
Oxidising properties	: No data available.

10. Stability and reactivity

10.1. Reactivity

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

10. Stability and reactivity (continued)

Reactivity : Not established.

10.2. Chemical stability

Chemical stability : Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions : Not established.

10.4. Conditions to avoid

Conditions to avoid : Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Materials to avoid : Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products : Fumes. Carbon monoxide. Carbon dioxide.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity

- **Inhalation** : Based on available data, the classification criteria are not met.
- **Dermal** : Based on available data, the classification criteria are not met.
- **Ingestion** : Based on available data, the classification criteria are not met.

Corrosion

: Based on available data, the classification criteria are not met.

Irritation

: Based on available data, the classification criteria are not met.

Sensitization

: May cause an allergic skin reaction.

Mutagenicity

: Based on available data, the classification criteria are not met.

Carcinogenicity

: Suspected of causing cancer.

Toxic for reproduction

: Based on available data, the classification criteria are not met.

STOT-single exposure

: Based on available data, the classification criteria are not met.

STOT-repeated exposure

: Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

: Based on available data, the classification criteria are not met.

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

12. Ecological information

12.1. Toxicity

Toxicity information : Harmful to aquatic life with long lasting effects.

12.2. Persistence - degradability

Persistence - degradability : May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Bioaccumulative potential : Not established.

12.4. Mobility in soil

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions : Avoid release to the environment.

13. Disposal considerations

13.1. Waste treatment methods

General : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
 Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

14. Transport information

14.1. Land transport (ADR-RID)

Proper shipping name : METAL POWDER, FLAMMABLE, N.O.S.
UN N° : 3089
H.I. nr : 40
ADR - Class : 4.1

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

14. Transport information (continued)

Labelling - Transport : 4.1 : Flammable solids, self-reactive substances and desensitized explosives.



ADR - Classification code : F3
F3

ADR - Group : II

ADR - Packing instructions : P002

ADR - Limited Quantity : 1 KG

ADR - Tunnel code



: E : Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name : METAL POWDER, FLAMMABLE, N.O.S.

UN N° : 3089

IMO-IMDG - Class or division : 4.1 : Flammable solids, self-reactive substances and desensitized explosives.

IMO-IMDG - Packing group : II

IMO-IMDG - Packing instructions : P002

IMO-IMDG - Limited quantities : 1 kg

IMO-IMDG - Marine pollution : No

EMS-Nr : F-G S-G

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name : METAL POWDER, FLAMMABLE, N.O.S.

UN N° : 3089

IATA - Class or division : 4.1 : Flammable solids, self-reactive substances and desensitized explosives.

IATA - Packing group : II

IATA - Passenger and Cargo Aircraft : ALLOWED

- Passenger and Cargo - Packing instruction : 445

- Passenger and Cargo - Maximum Quantity/Packing : 15 kg

IATA - Cargo only : ALLOWED

- Cargo only - Packing instruction : 448

- Cargo only - Maximum Quantity/Packing : 50 kg

MATERIAL SAFETY DATA SHEET (MSDS)

NICKEL METAL POWDER (APP. 300 MESH)

14. Transport information (continued)

IATA - Limited Quantities : 5 kg
 ERG-Nr : 3L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental regulations/legislation specific for the substance or mixture : Ensure all national/local regulations are observed.

REACH Restrictions - Annex XVII : With the exception of those listed below:
 Annex XVII
 The components of this product are not subject to restrictions.

REACH Authorisation - Annex XIV : The components of this product are not subject to authorization.

15.2. Chemical Safety Assessment

Chemical Safety Assessment : It has not been carried out.

16. Other information

Revision : Revision - See : *

Abbreviations and acronyms : PBT: persistent, bioaccumulative and toxic.
 vPvB: very persistent and very bioaccumulative

Sources of key data used : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

List of relevant R phrases (heading 3) : R40 : Limited evidence of a carcinogenic effect.
 R43 : May cause sensitization by skin contact.
 R48/23 : Toxic : danger of serious damage to health by prolonged exposure through inhalation.
 R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of full text of H-statements in section 3 : H317 : May cause an allergic skin reaction.
 H351 : Suspected of causing cancer.
 H372 : Causes damage to organs through prolonged or repeated exposure.
 H412 : Harmful to aquatic life with long lasting effects.

Further information : None.

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)
NICKEL METAL POWDER (APP. 300 MESH)

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
 - **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
 - **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.
-

End of document