

#### CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

### POLYVINYL PYROLIDIONE K30 (PVP) M.W. APPROX 40000

#### **1. Product Identification**

Synonyms: Polyvinyl alcohol; PVA; Polyvinol; ethenol homopolymer CAS No.: 9002-89-5

Product Coad: P0163405000

Molecular Weight: Not applicable to mixtures. Chemical Formula: [ -CH2CHOH- ]n

#### 2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Methyl Alcohol	67-56-1	< 1%	No
Polyvinyl Alcohol	9002-89-5	> 95%	Yes

#### 3. Hazards Identification

Emergency Overview CAUTION! MAY FORM COMBUSTIBLE DUST CONCENTRATIONS IN AIR. NUISANCE DUST. Health Rating: 0 - None Flammability Rating: 2 - Moderate Reactivity Rating: 0 - None Contact Rating: 0 - None Lab Protective Equip: GOGGLES; LAB COAT; CLASS B EXTINGUISHER Storage Color Code: Red (Flammable) Potential Health Effects

**Inhalation:** Dust may be formed under certain conditions of use. Treat as a nuisance dust. When heated above 200C, fumes irritating the eyes nose, throat will be evolved. Symptoms may include tears in the eyes with itching, redness, burning pain in throat and nose.

Ingestion: Not expected to be a health hazard via ingestion.

Skin Contact: Not expected to be a health hazard from skin exposure.

Eye Contact: Mechanical irritation only.

**Chronic Exposure:** No human data. Animal studies showed a drop in hemoglobin and erythrocyte(red blood cell) number with eventual complete coagulation inhibition. There is the possibility of carcinogenicity as seen in some animal studies. **Aggravation of Pre-existing Conditions:** No information found.

#### 4. First Aid Measures

Inhalation: Remove to fresh air. Get medical attention for any breathing difficulty.
 Ingestion: Not expected to require first aid measures.
 Skin Contact: Wash exposed area with soap and water. Get medical advice if irritation develops.
 Eye Contact: Wash thoroughly with running water. Get medical advice if irritation develops.

#### 5. Fire Fighting Measures

Fire: Flash point: 79C (174F) OC

As with most organic solids, fire is possible at elevated temperatures or by contact with an ignition source. Minimum dust cloud ignition temperature: 450C (842F).

**Explosion:** Fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Maximum explosion pressure: 78 lb./sq. in.

Fire Extinguishing Media: Water spray, dry chemical, alcohol foam, or carbon dioxide.

**Special Information:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

#### 6. Accidental Release Measures

Remove all sources of ignition. Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Clean up spills in a manner that does not disperse dust into the air. Use non-sparking tools and equipment. Reduce airborne dust and prevent scattering by moistening with water. Pick up spill for recovery or disposal and place in a closed container.



#### CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

## POLYVINYL PYROLIDIONE K30 (PVP) M.W. APPROX 40000

#### 7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Separate from incompatibilities. Avoid dust formation and control ignition sources. Employ grounding, venting and explosion relief provisions in accord with accepted engineering practices in any process capable of generating dust and/or static electricity. Empty only into inert or non-flammable atmosphere. Emptying contents into a non-inert atmosphere where flammable vapors may be present could cause a flash fire or explosion due to electrostatic discharge.

#### 8. Exposure Controls/Personal Protection

#### Airborne Exposure Limits: None established.

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.
 Personal Respirators (NIOSH Approved): For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH type N95 or better filters) may be worn. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-face positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.
 Skin Protection: Wear protective gloves and clean body-covering clothing.
 Eye Protection: Use chemical safety goggles.

#### 9. Physical and Chemical Properties

Appearance: White free-flowing granules. Odor: Mild odor. Solubility: Moderately soluble. Specific Gravity: 1.19 - 1.31 pH: Aqueous solution is neutral or slightly acid. % Volatiles by volume @ 21C (70F): 0 Boiling Point: No information found. Melting Point: ca. 200C (ca. 392F) Vapor Density (Air=1): No information found. Vapor Pressure (mm Hg): No information found. Evaporation Rate (BuAc=1): No information found.

#### 10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.
Hazardous Decomposition Products: Complete combustion will emit carbon dioxide and water when heated to decomposition. Incomplete combustion gives in addition carbon monoxide and oxidation products, including organic acids, aldehydes and alcohol.
Hazardous Polymerization: Will not occur.
Incompatibilities: Strong oxidizers.
Conditions to Avoid: Heat, flame, ignition sources, dusting and incompatibles.

#### **11. Toxicological Information**

Oral rat LD50: > 20 gm/kg. Investigated as a tumorigen.

---NTP Carcinogen---

Ingredient	Known	Anticip	ated	IARC Category
Methyl Alcohol (67-56-1)	N	0	No	None
Polyvinyl Alcohol (9002-89-	-5)	No	No	3

#### **12. Ecological Information**

Environmental Fate: No information found. Environmental Toxicity: No information found.



#### CHAITANYA CH5, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS) POLYVINYL PYROLIDIONE K30 (PVP) M.W. APPROX 40000

#### **13. Disposal Considerations**

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

#### 14. Transport Information

Not regulated.

#### **15. Regulatory Information**

Characterite and the second se

\Chemical Inventory Status - Part 1\				
Ingredient	TSCA EC Japan Australia			
Methyl Alcohol (67-56-1)	Yes Yes Yes Yes			
Polyvinyl Alcohol (9002-89-5)	Yes No Yes Yes			
\Chemical Inventory Status - Part 2\				
	Canada			
Ingredient	Korea DSL NDSL Phil.			
Methyl Alcohol (67-56-1)	Yes Yes No Yes			
Polyvinyl Alcohol (9002-89-5)	Yes Yes No Yes			
\Federal, State & International Regulations - Part 1\				
-SARA	A 302SARA 313			
Ingredient RC	Q TPQ List Chemical Catg.			
Methyl Alcohol (67-56-1)	No No Yes No			
Polyvinyl Alcohol (9002-89-5) No No No No				
\Federal, State & International Regulations - Part 2\				
	-RCRATSCA-			
Ingredient CE	ERCLA 261.33 8(d)			
Methyl Alcohol (67-56-1) 5000 U154 No				
Polyvinyl Alcohol (9002-89-5)	No No No			
Chemical Weapons Convention: No TSCA 12(b): No CDTA: No				
SARA 311/312: Acute: No Chronic: No Fire: Yes Pressure: No				
Reactivity: No (Mixture / Solid)				

Australian Hazchem Code: None allocated. Poison Schedule: None allocated. WHMIS: This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

### AN ISO 9001: 2015 CERTIFIED



CHAITANYA CH5, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

## POLYVINYL PYROLIDIONE K30 (PVP) M.W. APPROX 40000

#### 16. Other Information

NFPA Ratings: Health: 0 Flammability: 2 Reactivity: 0 Label Hazard Warning: CAUTION! MAY FORM COMBUSTIBLE DUST CONCENTRATIONS IN AIR. NUISANCE DUST. Label Precautions: Store in a tightly closed container. Avoid breathing dust. Avoid dust cloud in presence of an ignition source. Maintain adequate ventilation. Label First Aid: Not applicable. Product Use: Laboratory Reagent.

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

#### DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation
  as to its comprehensiveness or accuracy. This document is intended only as a guide to the
  appropriate precautionary handling of the material by a properly trained person using this
  product.

End of document