

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

**MATERIAL SAFETY DATA SHEET (MSDS)****POTASSIUM DICHROMATE LR****1. Product Identification**

**Synonyms:** Dichromic Acid, Dipotassium Salt; Potassium Bichromate; Dipotassium Dichromate  
**CAS No.:** 7778-50-9

Product Coad: P0166000500

**Molecular Weight:** 294.18  
**Chemical Formula:** K<sub>2</sub>Cr<sub>2</sub>O<sub>7</sub>

**2. Composition/Information on Ingredients**

Ingredient	CAS No	Percent	Hazardous
Potassium Dichromate	7778-50-9	99 - 100%	Yes

**3. Hazards Identification**

**Emergency Overview** POISON! DANGER! MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE A FIRE. CORROSIVE. CAUSES SEVERE BURNS TO EVERY AREA OF CONTACT. AFFECTS THE RESPIRATORY SYSTEM, LIVER, KIDNEYS, EYES, SKIN AND BLOOD. MAY CAUSE ALLERGIC REACTION. CANCAUSE CANCER. Risk of cancer depends on duration and level of exposure.

**Inhalation:** Corrosive. Extremely destructive to tissues of the mucous membranes and upper respiratory tract. May cause ulceration and perforation of the nasal septum. Symptoms may include sore throat, coughing, shortness of breath, and labored breathing. May produce pulmonary sensitization or allergic asthma. Higher exposures may cause pulmonary edema.

**Ingestion:** Corrosive. Swallowing can cause severe burns of the mouth, throat, and stomach, leading to death. Can cause sore throat, vomiting, diarrhea. May cause violent gastroenteritis, peripheral vascular collapse, dizziness, intense thirst, muscle cramps, shock, coma, abnormal bleeding, fever, liver damage and acute renal failure.

**Skin Contact:** Corrosive. Symptoms of redness, pain, and severe burn can occur. Dusts and strong solutions may cause severe irritation. Contact with broken skin may cause ulcers (chrome sores) and absorption, which may cause systemic poisoning, affecting kidney and liver functions. May cause skin sensitization. Highly Toxic! May be absorbed through the skin; symptoms may parallel ingestion.

**Eye Contact:** Corrosive. Contact can cause blurred vision, redness, pain and severe tissue burns. May cause corneal injury or blindness.

**Chronic Exposure:** Repeated or prolonged exposure can cause ulceration and perforation of the nasal septum, respiratory irritation, liver and kidney damage and ulceration of the skin. Ulcerations at first may be painless, but may penetrate to the bone producing "chrome holes." Known to be a human carcinogen.

**Aggravation of Pre-existing Conditions:** Persons with pre-existing skin disorders, asthma, allergies or known sensitization to chromic acid or chromates may be more susceptible to the effects of this material.

**4. First Aid Measures**

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**Ingestion:** If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Skin Contact:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

**5. Fire Fighting Measures**

**Fire:** Not combustible, but substance is a strong oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. Releases oxygen, upon decomposition, which enhances combustion.

**Explosion:** Contact with oxidizable substances may cause extremely violent combustion.

**Fire Extinguishing Media:** Flood with large amounts of water. Water spray may be used to keep fire exposed containers cool. Do not allow water runoff to enter sewers or waterways.

**Special Information:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

**6. Accidental Release Measures**

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### POTASSIUM DICHROMATE LR

#### 7. Handling and Storage

Protect against physical damage. Store in a dry location separate from combustible, organic or other readily oxidizable materials. Avoid storage on wood floors. Remove and dispose of any spilled dichromates; do not return to original containers. Wear special protective equipment (Sec. 8) for maintenance break-in or where exposures may exceed established exposure levels. Wash hands, face, forearms and neck when exiting restricted areas. Shower, dispose of outer clothing, change to clean garments at the end of the day. Avoid cross-contamination of street clothes. Wash hands before eating and do not eat, drink, or smoke in workplace. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

#### 8. Exposure Controls/Personal Protection

**Airborne Exposure Limits:** - OSHA Permissible Exposure Limit (PEL):

For chromic acid and chromates, as CrO<sub>3</sub> = 0.1 mg/m<sup>3</sup> (ceiling)

- ACGIH Threshold Limit Value (TLV):

For water-soluble Cr(VI) compounds, as Cr = 0.05 mg/m<sup>3</sup> (TWA), A1 - confirmed human carcinogen.

**Ventilation System:** A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

**Personal Respirators (NIOSH Approved):** If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

**Skin Protection:** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Eye Protection:** Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

#### 9. Physical and Chemical Properties

**Appearance:** Orange-red crystals or powder

**Odor:** Odorless.

**Solubility:** 6.5% @ 10C (50F) in water.

**Specific Gravity:** 2.676 @ 25C/4C

**pH:** 4.04 (1% aq. solution) 3.57 (10% aq. solution)

**% Volatiles by volume @ 21C (70F):** 0

**Boiling Point:** 500C (932F)

**Melting Point:** 398C (748F)

#### 10. Stability and Reactivity

**Stability:** Stable under ordinary conditions of use and storage.

**Hazardous Decomposition Products:** Burning may produce chrome oxides.

**Hazardous Polymerization:** Will not occur.

**Incompatibilities:** Reducing agents, acetone plus sulfuric acid, boron plus silicon, ethylene glycol, iron, hydrazine, and hydroxylamine. Any combustible, organic or other readily oxidizable material (paper, wood, sulfur, aluminum or plastics).

**Conditions to Avoid:** Heat, incompatibles.

#### 11. Toxicological Information

Oral rat LD50: 25 mg/kg. Skin rabbit LD50: 14 mg/kg Investigated as a tumorigen, mutagen, reproductive effector.

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category
Potassium Dichromate (7778-50-9)	Yes	No	1

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### POTASSIUM DICHROMATE LR

#### 12. Ecological Information

**Environmental Fate:** When released into the soil, this material may leach into groundwater. When released into water, this material is not expected to evaporate significantly. This material may bioaccumulate to some extent. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition.

**Environmental Toxicity:** No information found.

#### 13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

#### 14. Transport Information

##### Domestic (Land, D.O.T.)

**Proper Shipping Name:** RQ, TOXIC, SOLID, OXIDIZING, N.O.S. (POTASSIUM DICHROMATE)

**Hazard Class:** 6.1, 5.1

**UN/NA:** UN3086

**Packing Group:** I

##### International (Water, I.M.O.)

**Proper Shipping Name:** TOXIC, SOLID, OXIDIZING, N.O.S. (POTASSIUM DICHROMATE)

**Hazard Class:** 6.1, 5.1

**UN/NA:** UN3086

**Packing Group:** I

#### 15. Regulatory Information

-----\Chemical Inventory Status - Part 1\-----

Ingredient	TSCA	EC	Japan	Australia
Potassium Dichromate (7778-50-9)	Yes	Yes	Yes	Yes

-----\Chemical Inventory Status - Part 2\-----

--Canada--

Ingredient	Korea	DSL	NDSL	Phil.
Potassium Dichromate (7778-50-9)	Yes	Yes	No	Yes

-----\Federal, State & International Regulations - Part 1\-----

-SARA 302- -----SARA 313-----

Ingredient	RQ	TPQ	List	Chemical Catg.
Potassium Dichromate (7778-50-9)	No	No	No	Chromium com

-----\Federal, State & International Regulations - Part 2\-----

-RCRA- -TSCA-

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### POTASSIUM DICHROMATE LR

Ingredient CERCLA 261.33 8(d)  
 Potassium Dichromate (7778-50-9) 10 No No  
 Chemical Weapons Convention: No TSCA 12(b): Yes CDTA: Yes  
 SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No  
 Reactivity: Yes (Pure / Solid)

#### WARNING:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

**Australian Hazchem Code:** 1WE

**Poison Schedule:** S6

#### WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

#### 16. Other Information

**NFPA Ratings:** Health: 3 Flammability: 1 Reactivity: 1 Other: **Oxidizer**

**Label Hazard Warning:** POISON! DANGER! MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE A FIRE. CORROSIVE. CAUSES SEVERE BURNS TO EVERY AREA OF CONTACT. AFFECTS THE RESPIRATORY SYSTEM, LIVER, KIDNEYS, EYES, SKIN AND BLOOD. MAY CAUSE ALLERGIC REACTION. CANCER HAZARD. CAN CAUSE CANCER. Risk of cancer depends on duration and level of exposure.

**Label Precautions:** Keep from contact with clothing and other combustible materials. Do not get in eyes, on skin, or on clothing. Do not breathe dust or mist from solutions. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Store in a tightly closed container. Do not store near combustible materials.

**Label First Aid:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. In all cases get medical attention immediately.

**Product Use:** Laboratory Reagent.

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

#### DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

**End of document**