

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

## POTASSIUM HYDROXIDE POWDER LR

#### 1. Product Identification

Synonyms: Caustic potash; potassium hydrate

CAS No.: 1310-58-3

Product Coad: P0167905000

Molecular Weight: 56.11 Chemical Formula: KOH

#### 2. Composition/Information on Ingredients

Ingredient CAS No Percent Hazardous

Potassium Hydroxide 1310-58-3 85 - 90% Yes

#### 3. Hazards Identification

Emergency Overview POISON! DANGER! CORROSIVE. CAUSES SEVERE BURNS TO SKIN, EYES, RESPIRATORY TRACT, AND GASTROINTESTINAL TRACT. MATERIAL IS EXTREMELY DESTRUCTIVE TO ALL BODY TISSUES. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED.

Potential Health Effects: Inhalation: Severe irritant. Effects from inhalation of dust or mist vary from mild irritation to serious damage of the upper respiratory tract, depending on the severity of exposure. Symptoms may include coughing, sneezing, damage to the nasal or respiratory tract. High concentrations can cause lung damage. Ingestion: Toxic! Swallowing may cause severe burns of mouth, throat and stomach. Other symptoms may include vomiting, diarrhea. Severe scarring of tissue and death may result. Estimated lethal dose: 5 grams. Skin Contact: Corrosive! Contact with skin can cause irritation or severe burns and scarring with greater exposures. Eye Contact: Highly Corrosive! Causes irritation of eyes with tearing, redness, swelling. Greater exposures cause severe burns with possible blindness resulting. Chronic Exposure: Prolonged contact with dilute solutions or dust of potassium hydroxide has a destructive effect on tissue. Aggravation of Pre-existing Conditions: Persons with pre-existing skin disorders or eye problems or impaired respiratory function may be more susceptible to the effects of the substance.

### 4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. Ingestion: If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately. Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

### 5. Fire Fighting Measures

Fire: Not combustible, but contact with water or moisture may generate enough heat to ignite combustibles. Explosion: Can react with chemically reactive metals such as aluminum, zinc, magnesium, copper, etc. to release hydrogen gas which can form explosive mixtures with air. Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire. Special Information: Solution process causes formation of corrosive mists. Hot or molten material can react violently with water. In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

## 6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust. Do not flush caustic residues to the sewer. Residues from spills can be diluted with water, neutralized with dilute acid such as acetic, hydrochloric or sulfuric. Absorb neutralized caustic residue on clay, vermiculite or other inert substance and package in a suitable container for disposal.

US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.



CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

## POTASSIUM HYDROXIDE POWDER LR

### 7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Protect from moisture. Addition to water releases heat which can result in violent boiling and spattering. Always add slowly and in small amounts. Never use hot water. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

#### 8. Exposure Controls/Personal Protection

#### **Airborne Exposure Limits:**

- OSHA Permissible Exposure Limit (PEL):

2 mg/m3 Ceiling

- ACGIH Threshold Limit Value (TLV):

2 mg/m3 Ceiling

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. Personal Respirators (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. Skin Protection: Rubber or neoprene gloves and additional protection including impervious boots, apron, or coveralls, as needed in areas of unusual exposure.

Eye Protection: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

### 9. Physical and Chemical Properties

Appearance: White deliquescent solid; Odor: Odorless.

Solubility: 52.8% in water @ 20C (68F)

Specific Gravity: 2.04 pH: 13.5 (0.1 molar solution)

% Volatiles by volume @ 21C (70F): 0

Boiling Point: 1320C (2408F) Melting Point: 360C (680F)

Vapor Pressure (mm Hg): 1.0 @ 714C (1317F)

# 10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products: Carbon monoxide when reacting with carbohydrates, and hydrogen gas when reacting with aluminum, zinc and tin. Thermal oxidation can produce toxic fumes of potassium oxide (K2O).

Hazardous Polymerization: Will not occur.

**Incompatibilities:** Contact with water, acids, flammable liquids and organic halogen compounds, especially trichloroethylene, may cause fire or explosion. Contact with nitromethane and other similar nitro compounds cause formation of shock sensitive salts. Contact with metals such as aluminum, tin and zinc causes formation of flammable hydrogen gas.

Conditions to Avoid: Heat, moisture, incompatibles.

## 11. Toxicological Information

For potassium hydroxide: Oral rat LD50: 273 mg/kg; Investigated as a mutagen. Skin Irritation Data (std Draize, 50 mg/24 H): Human, Severe; Rabbit, Severe. Eye Irritation Data(Rabbit, non-std test,1 mg/24 H, rinse): Moderate.

---NTP Carcinogen---

Ingredient Known Anticipated IARC Category



CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

## POTASSIUM HYDROXIDE POWDER LR

Potassium Hydroxide (1310-58-3)		No	No	None
Water (7732-18-5)	No	No		None

#### 12. Ecological Information

Environmental Fate: No information found.

Environmental Toxicity: Potassium Hydroxide: TLm: 80 ppm/Mosquito fish/ 24 hr./ Fresh water

### 13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

### 14. Transport Information

## International (Water, I.M.O.)

Proper Shipping Name: POTASSIUM HYDROXIDE, SOLID

Hazard Class: 8 UN/NA: UN1813 Packing Group: II

## 15. Regulatory Information

\Chemical Inventory Status	- Part 1\				
Ingredient	TSCA EC Japan Australia				
Potassium Hydroxide (1310-58-3)	Yes Yes Yes Yes				
Water (7732-18-5)	Yes Yes Yes Yes				
\Chemical Inventory Status - Part 2\					
	Canada				
Ingredient	Korea DSL NDSL Phil.				
Potassium Hydroxide (1310-58-3)	Yes Yes No Yes				
Water (7732-18-5)	Yes Yes No Yes				
\Federal, State & International Regulations - Part 1\					
-SARA	302SARA 313				
Ingredient RC	TPQ List Chemical Catg.				
Potassium Hydroxide (1310-58-3)	No No No No				
Water (7732-18-5)	No No No No				



CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

## POTASSIUM HYDROXIDE POWDER LR

-----\Federal, State & International Regulations - Part 2\-----

-RCRA- -TSCA-

Ingredient CERCLA 261.33 8(d)

Potassium Hydroxide (1310-58-3) 1000 No No

Water (7732-18-5) No No No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No

SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No

Reactivity: Yes (Mixture / Solid)

Australian Hazchem Code: 2R

Poison Schedule: S6

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

### 16. Other Information

NFPA Ratings: Health: 3 Flammability: 0 Reactivity: 1

Label Hazard Warning:

POISON! DANGER! CORROSIVE. CAUSES SEVERE BURNS TO SKIN, EYES, RESPIRATORY TRACT, AND GASTROINTESTINAL TRACT. MATERIAL IS EXTREMELY DESTRUCTIVE TO ALL BODY TISSUES. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED.

Label Precautions:

Do not get in eyes, on skin, or on clothing.

Do not breathe dust.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Label First Aid:

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. In all cases get medical attention immediately.

In accordance with REACH Regulation (CE) No 1907/2006 and with CLP Regulation (CE) No 1272/2008

## DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- · SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document