

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM PERMANGANATE LR CRYSTALS

1. Product Identification

Synonyms: Permanganic acid, potassium salt; Condy's crystals

CAS No.: 7722-64-7

Product Coad: P0168600500

Molecular Weight: 158.03 Chemical Formula: KMnO4

2. Composition/Information on Ingredients

Ingredient CAS No Percent Hazardous

Potassium Permanganate 7722-64-7 90 - 100% Yes

3. Hazards Identification

Emergency Overview

DANGER! STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. HARMFUL IF SWALLOWED OR INHALED.

Potential Health Effects

Inhalation: Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. High concentrations can cause pulmonary edema.

Ingestion: Ingestion of solid or high concentrations causes severe distress of gastro-intestinal system with possible burns and edema; slow pulse; shock with fall of blood pressure. May be fatal. Ingestion of concentrations up to 1% causes burning of the throat, nausea, vomiting, and abdominal pain; 2-3% causes anemia and swelling of the throat with possible suffocation; 4-5% may cause kidney damage.

Skin Contact: Dry crystals and concentrated solutions are caustic causing redness, pain, severe burns, brown stains in the contact area and possible hardening of outer skin layer. Diluted solutions are only mildly irritating to the skin.

Eye Contact: Eye contact with crystals (dusts) and concentrated solutions causes severe irritation, redness, blurred vision and can cause severe damage, possibly permanent.

Chronic Exposure: Prolonged skin contact may cause irritation, defatting, and dermatitis. Chronic manganese poisoning can result from excessive inhalation exposure to manganese dust and involves impairment of the central nervous system. Early symptoms include sluggishness, sleepiness, and weakness in the legs. Advanced cases have shown symptoms of fixed facial expression, emotional disturbances, spastic gait, and falling. **Aggravation of Pre-existing Conditions:** No information found.

4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. Ingestion: If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire: Not combustible, but substance is a strong oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. Contact with oxidizable substances may cause extremely violent combustion. **Explosion:** Strong oxidants may explode when shocked, or if exposed to heat, flame, or friction. Also may act as initiation source for dust or vapor explosions. Contact with oxidizable substances may cause extremely violent combustion. Sealed containers may rupture when heated. Sensitive to mechanical impact. **Fire Extinguishing Media:** Use water spray to blanket fire, cool fire exposed containers, and to flush non-ignited spills or vapors away from fire. Suffocating type extinguishers are not as effective as water. Do not allow water runoff to enter sewers or waterways.

Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Remove all sources of ignition. Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Clean up spills in a manner that does not disperse dust into the air. Use non-sparking tools and equipment. Reduce airborne dust and prevent scattering by moistening with water. Pick up spill for recovery or disposal and place in a closed container. US Regulations (CERCLA) require reporting spills and



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM PERMANGANATE LR CRYSTALS

releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage and moisture. Isolate from any source of heat or ignition. Avoid storage on wood floors. Separate from incompatibles, combustibles, organic or other readily oxidizable materials. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

- OSHA Permissible Exposure Limit (PEL):
- 5 mg/m3 Ceiling for manganese compounds as Mn
- ACGIH Threshold Limit Value (TLV):
- 0.2 mg/m3 (TWA) for manganese, elemental and inorganic compounds as Mn

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: Purple-bronze crystals.

Odor: Odorless. Solubility: 7 g in 100 g of water.

Density: 2.7

pH: No information found.

% Volatiles by volume @ 21C (70F): 0 Boiling Point: Not applicable. Melting Point: ca. 240C (ca. 464F) Vapor Density (Air=1): 5.40

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Toxic metal fumes may form when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Powdered metals, alcohol, arsenites, bromides, iodides, phosphorous, sulfuric acid, organic compounds, sulfur, activated carbon, hydrides, strong hydrogen peroxide, ferrous or mercurous salts, hypophosphites, hyposulfites, sulfites, peroxides, and oxalates.

Conditions to Avoid:

Heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Investigated as a mutagen, reproductive effector. Oral rat LD50: 750 mg/kg.

---NTP Carcinogen---



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAŁ 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM PERMANGANATE LR CRYSTALS

Ingredient	Known	Anticipated		IARC Category	
Potassium Permanganate	e (7722-64	-7)	No	No	None

12. Ecological Information

Environmental Fate: No information found.

Environmental Toxicity: Dangerous to the environment. Very toxic to aquatic organisms; may cause long term adverse effects in the aquatic environment

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Proper Shipping Name: RQ, POTASSIUM PERMANGANATE

Hazard Class: 5.1 UN/NA: UN1490 Packing Group: II

15. Regulatory Information

\Chemical Inventory Status	s - Part 1\				-			
Ingredient	TSCA EC Japan Australia							
Potassium Permanganate (7722	-64-7)	Yes	Yes \	⁄es	Yes			
\Chemical Inventory Status - Part 2\								
Canada								
Ingredient	Korea DS	L NDS	L Phil.					
Potassium Permanganate (7722	-64-7)	Yes	Yes	No	Yes			
\Federal, State & International Regulations - Part 1\								
-SARA 302SARA 313								
Ingredient R	Q TPQ I	List Che	emical (Catg.				
Potassium Permanganate (7722-	64-7) No	o No	No	Mang	janese co			
\Federal, State & International Regulations - Part 2\								
	-RCRA	-TSCA-						
Ingredient C	ERCLA 26	61.33	8(d)					
Potassium Permanganate (7722	-64-7) 1	100	No	No				



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM PERMANGANATE LR CRYSTALS

Chemical Weapons Convention: No TSCA 12(b): No CDTA: Yes

SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No

Reactivity: No (Pure / Solid)

Australian Hazchem Code: 2Y

Poison Schedule: S6

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 1 Flammability: 0 Reactivity: 0 Other: Oxidizer

Label Hazard Warning:

DANGER! STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. HARMFUL IF SWALLOWED OR INHALED.

Label Precautions: Keep from contact with clothing and other combustible materials.

Store in a tightly closed container.

Do not store near combustible materials.

Remove and wash contaminated clothing promptly.

Do not get in eyes, on skin, or on clothing.

Do not breathe dust.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Label First Aid: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. In all cases get medical attention immediately.

Product Use: Laboratory Reagent.

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation
 as to its comprehensiveness or accuracy. This document is intended only as a guide to the
 appropriate precautionary handling of the material by a properly trained person using this
 product.

End of document