

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM THIOCYANATE LR (POTASSIUM SULPHOCYANIDE)

1. Product Identification

Synonyms: Potassium sulfocyanate; Potassium thiocyanide; Thiocyanic acid, potassium salt; Potassium isothiocyanate CAS No.: 333-20-0 Molecular Weight: 97.18 Chemical Formula: KSCN

Product Coad: P0170405000

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent
Potassium Thiocyanate	333-20-0	90 - 100%

3. Hazards Identification

Emergency Overview WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. Inhalation: Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. Ingestion: May cause psychosis, vomiting, disorientation, weakness, low blood pressure, convulsions and death which may be delayed. The probable lethal dose is between 15-30 grams. Skin Contact: Causes irritation to skin. Symptoms include redness, itching, and pain. Eye Contact: Causes irritation, redness, and pain. Chronic Exposure: Prolonged or repeated skin exposure may cause dermatitis. Repeated ingestion of small amounts may cause weakness, confusion, central nervous system effects, nausea and skin eruptions.

4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. Ingestion: Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention. Skin Contact: Wipe off excess material from skin then immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse. Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard. Explosion: Not considered to be an explosion hazard. Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire. Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. May emit toxic and flammable fumes of cyanide if involved in a fire.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from oxidizing materials. Store in the dark. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: None established.

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. **Personal Respirators (NIOSH Approved):** For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH type N95 or better filters) may be worn. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not

known, use a full-face positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. **Skin Protection:** Wear impervious protective

clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. **Eye Protection:** Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM THIOCYANATE LR (POTASSIUM SULPHOCYANIDE)

9. Physical and Chemical Properties

Appearance: Colorless, deliquescent crystals. Odor: Odorless. Solubility: Very soluble in water.

Density: 1.89 % Volatiles by volume @ 21C (70F): 0

Boiling Point: 500C (932F) Melting Point: 173C (343F)

10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage. Slowly decomposes on exposure to light. **Hazardous Decomposition Products:** Burning may produce nitrogen oxides, sulfur compounds, and possibly cyanides. **Hazardous Polymerization:** Will not occur. **Incompatibilities:** Strong oxidizers, active halogen compounds. **Conditions to Avoid:** Light and incompatibles.

11. Toxicological Information

Oral rat LD50: 854 mg/kg. Investigated as a mutagen, reproductive effector.

---NTP Carcinogen---

Ingredient Known Anticipated IARC Category

Potassium Thiocyanate (333-20-0) No No None

12. Ecological Information

Environmental Fate: No information found. Environmental Toxicity: No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Not regulated.

15. Regulatory Information

NA

16. Other Information

NFPA Ratings: Health: 3 Flammability: 0 Reactivity: 0

Label Hazard Warning: WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. Label Precautions: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing dust. Keep container closed. Use only with adequate ventilation.

Label First Aid: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. In case of contact, wipe off excess material from skin then immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In all cases, get medical attention.

Product Use: Laboratory Reagent.

OM SHREE GANESHYA NAMAH



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM THIOCYANATE LR (POTASSIUM SULPHOCYANIDE)

In accordance with REACH Regulation (CE) Nº 1907/2006 and with CLP Regulation (CE) Nº 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document