

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)**SILICA GEL 70-230 MESH (FOR COLUMN CHROMATOGRAPHY)****1. Product Identification**

Synonyms: Silica, amorphous; Silica, precipitated and gel)
CAS No.: 112926-00-8

Product Coad: S0180400500

Molecular Weight: Not applicable.

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Silica Ge 70-230 MESH	112926-00-8	> 99%	Yes

3. Hazards Identification**Emergency Overview**

CAUTION! MAY CAUSE IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT.

Potential Health Effects This product contains synthetic amorphous silica, not to be confused with crystalline silica such as quartz, cristobalite or tridymite or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms. **Inhalation:** May cause dryness and irritation to mucous membranes, nose, and throat. Symptoms may include coughing, sore throat, and wheezing. **Ingestion:** No adverse effects expected. **Skin Contact:** May cause irritation with dryness and abrasion. **Eye Contact:** May cause irritation, redness and pain. **Chronic Exposure:** Repeated exposure may cause symptoms similar to those listed for acute effects. Synthetic amorphous silica does not produce silicosis. Prolonged exposure to cobalt has been shown to cause cancer in laboratory animals.

4. First Aid Measures

Inhalation: Remove to fresh air. Get medical attention for any breathing difficulty.

Ingestion: Give several glasses of water to drink to dilute. If large amounts were swallowed, get medical advice. **Skin Contact:** Immediately flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if irritation develops. **Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention if irritation persists.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard. **Explosion:** Not considered to be an explosion hazard.

Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire. **Special Information:** Use protective clothing and breathing equipment appropriate for the surrounding fire.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. When pouring into a container of flammable liquid, ground both containers electrically to prevent a static electric spark. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

MATERIAL SAFETY DATA SHEET (MSDS)

SILICA GEL 70-230 MESH (FOR COLUMN CHROMATOGRAPHY)

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: Silica (synthetic, amorphous):- OSHA Permissible Exposure Limit (PEL) - 80/(%SiO₂) mg/m³ (TWA) for amorphous silica, including natural diatomaceous earth.

For Inorganic Cobalt Compounds:- ACGIH Threshold Limit Value (TLV) -

0.02 mg/m³ (TWA) as Co, A3: Animal carcinogen. **Ventilation System:** A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source,

preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. **Skin Protection:** Wear protective gloves and clean body-covering clothing.

Eye Protection: Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: WHITE.

Odor: Odorless.

10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage. **Hazardous Decomposition Products:** Oxides of carbon and silicon may be formed when heated to decomposition. **Hazardous Polymerization:** Will not occur. **Incompatibilities:** Reacts with hydrogen fluoride, fluorine, oxygen difluoride, chlorine trifluoride, strong acids, strong bases, and oxidizers. **Conditions to Avoid:** Moisture, extreme heat, and incompatibles.

11. TOXICOLOGICAL INFORMATION

N/A

12. ECOLOGICAL INFORMATION

Mobility:No data available. Bioaccumulation:No data available. Ecotoxicity effects:No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: Waste disposal must be in accordance with appropriate

Federal, State, and local regulations.

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)**SILICA GEL 70-230 MESH (FOR COLUMN CHROMATOGRAPHY)****14. TRANSPORT INFORMATION**

NOT REGULATED

15. REGULATORY INFORMATION

N/A

16. OTHER INFORMATION

NFPA Ratings: Health: 1 Flammability: 0 Reactivity: 0

Label Hazard Warning: CAUTION! MAY CAUSE IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT.

Label Precautions: Avoid contact with eyes, skin and clothing. Avoid breathing dust. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. **Label First Aid:** If inhaled, remove to fresh air. Get medical attention for any breathing difficulty. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists.

Product Use: Laboratory Reagent.

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document