

MATERIAL SAFETY DATA SHEET (MSDS)

SILICON METAL POWDER 200 MESH

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : SILICON METAL POWDER 200 MESH

Product code : S0180900500

Identification of the product : SILICON (METAL) POWDER 98.5%

CAS No: 7440-21-3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification SUVCHEM Chaitanya Tower, 2nd Floor, Office # 206,

Siddharth Nagar, S.V. Road,

Goregaon (West), Mumbai - 400062,

Maharashtra, India.

Contact: +91 22 28725393 / 94 / 95

Email ID: info@suvchem.com/care@suvchem.com

1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification : F; R11

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Physical hazards : Flammable solids - Category 1 - Danger (CLP : Flam. Sol. 1) H228

2.2. Label elements

Labelling EC 67/548 or EC 1999/45

Symbol(s)





MATERIAL SAFETY DATA SHEET (MSDS)

SILICON METAL POWDER 200 MESH

2. Hazards identification -DSD (continued)

Symbol(s) : F : Highly flammable R **Phrase(s)** : R11 : Highly flammable.

S Phrase(s) : S26 : In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S36: Wear suitable protective clothing.

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms

◈

Signal words : Danger

Hazard statements : H228 : Flammable solid.

Precautionary statements

Prevention : P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment.

P210: Keep away from heat, sparks, open flames or hot surfaces. - No smoking. P280: Wear protective gloves, protective clothing, eye protection, face protection.

• **Response** : P370+P378: In case of fire: Use for extinction.

2.3. Other hazards

Other hazards : The substance does not fulfil the criteria to be identified as PBT substance or vPvB

substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

Substance / Preparation : SILICON (METAL) POWDER 98.5%

Substance.

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures

4.1. Description of first aid measures

Inhalation : Assure fresh air breathing. Allow the victim to rest.

Skin contact : Remove affected clothing and wash all exposed skin area with mild soap and

water, followed by warm water rinse.

Eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or

redness persist.

Ingestion : Obtain emergency medical attention. Do NOT induce vomiting. Rinse mouth.



MATERIAL SAFETY DATA SHEET (MSDS)

SILICON METAL POWDER 200 MESH

4. First aid measures (continued)

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use : Not expected to present a significant hazard under anticipated conditions of normal

use

Not expected to present a significant hazard under anticipated conditions of normal

use.

4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person. If you feel unwell, seek

medical advice (show the label where possible).

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

Surrounding fires : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

Flammable class : Flammable solid.

Hazardous combustion products : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory

protection.

Special procedures : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to

enter environment.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection.

Ventilate area.

Technical measures : Use special care to avoid static electric charges.

Special precautions : Remove ignition sources. No naked lights. No smoking. **For non-emergency personnel** : Evacuate unnecessary personnel.

6.2. Environmental precautions



MATERIAL SAFETY DATA SHEET (MSDS)

SILICON METAL POWDER 200 MESH

6. Accidental release measures (continued)

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters

sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods : On land, sweep or shovel into suitable containers. Minimize generation of dust.

Store away from other materials.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling

Handling : Wash hands and other exposed areas with mild soap and water before eat, drink or

smoke and when leaving work.

Handle empty containers with care because residual vapours are flammable.

Technical protective measures : Provide good ventilation in process area to prevent formation of vapour.

Proper grounding procedures to avoid static electricity should be followed. Use

explosion-proof electrical, ventilating, lighting, ..., equipment.

Special precautions: No naked lights. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep only in the original container in a cool, well ventilated place. Keep container

closed when not in use. Keep in fireproof place. Ground/bond container and

receiving equipment.

Storage - away from : Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Specific end use(s) : None.

8. Exposure controls/personal protection

8.1. Exposure controls

Personal protection : Avoid all unnecessary exposure.

Respiratory protectionHand protectionWear approved mask.Wear protective gloves.

• Eye protection : Chemical goggles or safety glasses.



MATERIAL SAFETY DATA SHEET (MSDS)

SILICON METAL POWDER 200 MESH

8. Exposure controls/personal protection (continued)

• Others : When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits : No data available.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state at 20 °C : Solid.

Colour : Blackish grey powder

Odour : Odorless

Odour threshold : No data available.

pH value : Not applicable.

Melting point [°C] : 1410°C

Decomposition point [°C] : N/A

Decomposition point [°C] : N/A

Critical temperature [°C] : N/A

Auto-ignition temperature [°C] : 780°C

Flammability (solid, gas) : N/A

Flammable solid.

: N/A Flash point [°C] **Boiling point [°C]** : 2355°C : N/A Initial boiling point [°C] : N/A Final boiling point [°C] : N/A **Evaporation rate** : N/A Vapour pressure [20°C] : N/A Vapour pressure mm/Hg : N/A Vapour density : 2,33 Density [g/cm3] Relative density, gas (air=1) : N/A Relative density, liquid (water=1) : N/A

Solubility in water [% weight] : Insoluble in water

Solubility in water : N/A

Log Pow octanol / water at 20°C : No data available.

Solubility : N/A Viscosity at 40°C [mm2/s] : N/A

9.2. Other information



MATERIAL SAFETY DATA SHEET (MSDS) SILICON METAL POWDER 200 MESH

9. Physical and chemical properties (continued)

Explosive properties : N/A
Explosion limits - upper [%] : N/A
Explosion limits - lower [%] : N/A

Oxidising properties : No data available.

10. Stability and reactivity

10.1. Reactivity

Reactivity : Not established.

10.2. Chemical stability

Chemical stability : Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions : Not established.

10.4. Conditions to avoid

Conditions to avoid : Direct sunlight. Extremely high or low temperatures. Open flame. Overheating.

Heat. Sparks.

10.5. Incompatible materials

Materials to avoid : Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products: Fumes. Carbon monoxide. Carbon dioxide.

May release flammable gases.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Inhalation
 Dermal
 Ingestion
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.



MATERIAL SAFETY DATA SHEET (MSDS) SILICON METAL POWDER 200 MESH

11. Toxicological information (continued)

Irritation : Based on available data, the classification criteria are not met. Sensitization : Based on available data, the classification criteria are not met. Mutagenicity : Based on available data, the classification criteria are not met. Carcinogenicity : Based on available data, the classification criteria are not met. **Toxic for reproduction** : Based on available data, the classification criteria are not met. : Based on available data, the classification criteria are not met. STOT-single exposure : Based on available data, the classification criteria are not met. STOT-repeated exposure **Aspiration hazard** : Based on available data, the classification criteria are not met.

12. Ecological information

12.1. Toxicity

Toxicity information : Not established.

12.2. Persistence - degradability

Persistence - degradability : Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential : Not established.

12.4. Mobility in soil

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment: The substance does not fulfil the criteria to be identified as PBT substance or vPvB

substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions : Avoid release to the environment.

13. Disposal considerations

13.1. Waste treatment methods

General : Avoid release to the environment. Dispose in a safe manner in accordance with

local/national regulations.



MATERIAL SAFETY DATA SHEET (MSDS) SILICON METAL POWDER 200 MESH

13. Disposal considerations (continued)

Special precautions : Handle empty containers with care because residual vapours are flammable.

14. Transport information

14.1. Land transport (ADR-RID)

Proper shipping name : SILICON POWDER, AMORPHOUS

UN N° : 1346 H.I. nr : 40 ADR - Class : 4.1

Labelling - Transport : 4.1 : Flammable solids, self-reactive substances and desensitized explosives.



ADR - Classification code : F3
ADR - Group : III

ADR - Packing instructions : P002 R001 LP002

ADR - Limited Quantity : 5 KG

ADR - Tunnel code



: E : Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name : SILICON POWDER, AMORPHOUS

UN N° : 1346

IMO-IMDG - Class or division : 4.1 : Flammable solids, self-reactive substances and desensitized explosives.

IMO-IMDG - Packing group : |||

IMO- IMDG - Packing instructions : P002 LP02
IMO-IMDG - Limited quantities : 5 kg
IMO-IMDG - Marine pollution : No
EMS-Nr : F-A S-G

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name : SILICON POWDER, AMORPHOUS

UN N° : 1346



MATERIAL SAFETY DATA SHEET (MSDS) **SILICON METAL POWDER 200 MESH**

14. Transport information (continued)

IATA - Class or division : 4.1 : Flammable solids, self-reactive substances and desensitized explosives.

IATA - Packing group

IATA - Passenger and Cargo Aircraft : ALLOWED

446

- Passenger and Cargo - Packing

instruction

- Passenger and Cargo - Maximum : 25 kg

Quantity/Packing

IATA - Cargo only : ALLOWED

- Cargo only - Packing instruction : 449 - Cargo only - Maximum Quantity/ : 100 kg

Packing

IATA - Limited Quantites : 10 kg **ERG-Nr** : 3L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

: Ensure all national/local regulations are observed. Safety, health and environmental

regulations/legislation specific for the

substance or mixture

REACH Restrictions - Annex XVII : The components of this product are not subject to restrictions. : The components of this product are not subject to authorization. **REACH Authorisation - Annex XIV**

15.2. Chemical Safety Assessment

: It has not been carried out. **Chemical Safety Assessment**

16. Other information

Revision : Revision - See : *

Abbreviations and acronyms : PBT: persistent, bioaccumulative and toxic.

vPvB: very persistent and very bioaccumulative

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF Sources of key data used

THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and

1999/45/EC, and amending Regulation (EC) No 1907/2006

Further information : None.

SILICON METAL POWDER 200 MESH OM SHREE GANESHYA NAMAH



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBA1 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

In accordance with REACH Regulation (CE) No 1907/2006 and with CLP Regulation (CE) No 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document