

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SILVER ACETATE LR (FOR SYNTHESIS)

1. Product Identification

Synonyms: Acetic acid, silver (1+) salt CAS No.: 563-63-3

Product Coad: S0182100025

Molecular Weight: 166.91 Chemical Formula: AqC2H3O2

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Silver Acetate	563-63-3	90 - 100	% Yes

3. Hazards Identification

Emergency Overview WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. Health Rating: 3 - Severe

Flammability Rating: 0 - None Reactivity Rating: 0 - None Contact Rating: 2 - Moderate Lab Protective Equip: GOGGLES; LAB COAT; VENT HOOD; PROPER GLOVES Storage Color Code: Green (General Storage) Potential Health Effects

Inhalation: Mild irritant and nuisance dust. Coughing, sneezing or possibly breathing difficulty upon the inhalation of large amounts.

Ingestion: Effect will be similar to but normally less severe than with silver nitrate. Acute poisoning can cause pain or burning sensation in mouth and throat, salivation, vomiting, diarrhea, methemoglobinemia, anuria and, in extreme cases, shock, coma and death.

Skin Contact: Causes irritation to skin. Symptoms include redness, itching, and pain.

Eye Contact: Possibly some chemical or mechanical irritation of the conjunctiva.

Chronic Exposure: Prolonged or repeated inhalation, application or ingestion of silver compounds may cause a permanent bluish discoloration of the skin and mucous membranes.

Aggravation of Pre-existing Conditions: Persons with heavy metals accumulation should cease contact with silver compounds.

4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. Ingestion: Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse. Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately. 5. Fire Fighting Measures

Fire: Not considered to be a fire hazard. Explosion: Not considered to be an explosion hazard. Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire. Special Information: Use protective clothing and breathing equipment appropriate for the surrounding fire.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802

7. Handling and Storage

Keep in a tightly closed light-resistant container, stored in a cool, dry, ventilated area. Protect against physical damage. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS) SILVER ACETATE LR (FOR SYNTHESIS)

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL): 0.01 mg/m3 (TWA) for silver metal dust and fume as Ag -ACGIH Threshold Limit Value (TLV):

0.01 mg /m3 (TWA) for soluble silver compounds as Ag

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. **Personal Respirators (NIOSH Approved):** If the exposure limit is exceeded and engineering controls are not feasible, a half-face high efficiency particulate respirator (NIOSH type N100 filter) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece high efficiency particulate respirator (NIOSH type N100 filter) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece high efficiency particulate respirator (NIOSH type N100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. **Skin Protection:** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. **Eye Protection:** Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: White to slightly grayish powder. Odor: Slight acidic odor. Solubility: 1.02g/100g water @ 20C (68F). Density: 3.26 pH: No information found. % Volatiles by volume @ 21C (70F): 0 Boiling Point: Decomposes. Melting Point: No information found. Vapor Density (Air=1): No information found. Vapor Pressure (mm Hg): No information found. Evaporation Rate (BuAc=1): No information found. 10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage. Light sensitive.
Hazardous Decomposition Products: May produce oxides of carbon and the contained metal.
Hazardous Polymerization: Will not occur.
Incompatibilities: Ammonia, ammonium hydroxide, acetylene, alkali metals.
Conditions to Avoid: Light, heat, incompatibles.

11. Toxicological Information

NTP Carcinogen				
Ingredient	Known	Anticipated	IARC Category	
	·			
Silver Acetate (563-63-3)	Ν	o No	None	

12. Ecological Information

Environmental Fate: No information found. Environmental Toxicity: No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SILVER ACETATE LR (FOR SYNTHESIS)

14. Transport Information

Not regulated.

15. Regulatory Information ------\Chemical Inventory Status - Part 1\------Ingredient TSCA EC Japan Australia Silver Acetate (563-63-3) Yes Yes Yes Yes -----\Chemical Inventory Status - Part 2\------Canada--Ingredient Korea DSL NDSL Phil. Silver Acetate (563-63-3) No Yes No Yes -----\Federal, State & International Regulations - Part 1\-----SARA 302- -----SARA 313-----Ingredient RQ TPQ List Chemical Catq. Silver Acetate (563-63-3) No No No Silver compo ------\Federal, State & International Regulations - Part 2\-------RCRA- -TSCA-Ingredient CERCLA 261.33 8(d) Silver Acetate (563-63-3) No No No Chemical Weapons Convention: No TSCA 12(b): No CDTA: No SARA 311/312: Acute: Yes Chronic: No Fire: No Pressure: No Reactivity: No (Pure / Solid)

Australian Hazchem Code: None allocated. Poison Schedule: None allocated. WHMIS: This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. <u>16. Other Information</u>

NFPA Ratings: Health: 1 Flammability: 0 Reactivity: 0

Label Hazard Warning: WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

Label Precautions: Wash thoroughly after handling. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Keep container closed. Use with adequate ventilation.

Label First Aid: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. In all cases, get medical attention. Product Use: Laboratory Reagent.



CHAITANYA CH5, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SILVER ACETATE LR (FOR SYNTHESIS)

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document