

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SILVER SULPHATE LR

1. Product Identification

Synonyms: Sulfuric Acid, disilver (1+) salt CAS No.: 10294-26-5

Product Coad: S0183900025

Molecular Weight: 311.74 Chemical Formula: Ag2 SO4

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent
Silver Sulfate	10294-26-5	90 - 100%

3. Hazards Identification

Emergency Overview WARNING! HARMFUL IF SWALLOWED.

Potential Health Effects

Inhalation: Exposures above the TLV may result in accumulation of silver in the body (argyria). Symptoms may include a permanent unsightly blue-gray pigmentation of the skin, mucous membranes and eyes.

Ingestion: Irritant to the mouth, throat, and stomach. Symptoms may include abdominal spasms, faintness, muscular spasms and argyria.

Skin Contact: May cause irritation.

Eye Contact: May cause irritation, discoloration.

Chronic Exposure: Prolonged or repeated inhalation, application or ingestion of silver compounds may cause a permanent bluish discoloration of the skin and mucous membranes.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

4. First Aid Measures

Inhalation: Remove to fresh air. Get medical attention for any breathing difficulty. Ingestion: Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Skin Contact: Wash exposed area with soap and water. Get medical advice if irritation develops. Eye Contact: Wash thoroughly with running water. Get medical advice if irritation develops.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard.

Explosion: Not considered to be an explosion hazard.

Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire.

Special Information: In the event of a fire, wear full protective clothing and NIOŠH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. May be sent to a licensed silver recovery firm or back to the supplier. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Keep in a tightly closed light-resistant container, stored in a cool, dry, ventilated area. Protect against physical damage. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: -OSHA Permissible Exposure Limit (PEL): 0.01 mg/m3 (TWA) for silver metal dust and fume as Ag -ACGIH Threshold Limit Value (TLV):0.01 mg /m3 (TWA) for soluble silver compounds as Ag Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CH5, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SILVER SULPHATE LR

exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half-face high efficiency particulate respirator (NIOSH type N100 filter) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece high efficiency particulate respirator (NIOSH type N100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Eye Protection: Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: Colorless to white crystals or crystalline powder. Odor: Odorless. Solubility: Slowly soluble in 125 parts water. Specific Gravity: 5.45 at 29C (84F) pH: No information found. % Volatiles by volume @ 21C (70F): 0 Boiling Point: 1085C (1985F) Melting Point: 652C (1206F) Vapor Density (Air=1):

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage. Darkens on exposure to air or light. Hazardous Decomposition Products: Oxides of sulfur and the contained metal. Hazardous Polymerization: Will not occur. Incompatibilities: No information found. Conditions to Avoid: Light.

11. Toxicological Information

---NTP Carcinogen---

Ingredient	Known	Anticip	ated IAI	RC Category
Silver Sulfate (10294-26-5)	Ν	lo I	No	None

12. Ecological Information

Environmental Fate: No information found. Environmental Toxicity: No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CH5, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SILVER SULPHATE LR

Not regulated. 15. Regulatory Information -----\Chemical Inventory Status - Part 1\-----Ingredient TSCA EC Japan Australia Silver Sulfate (10294-26-5) Yes Yes Yes Yes ------\Chemical Inventory Status - Part 2\-------Canada--Ingredient Korea DSL NDSL Phil. Silver Sulfate (10294-26-5) Yes Yes No Yes ------\Federal, State & International Regulations - Part 1\-------SARA 302- -----SARA 313-----Ingredient RQ TPQ List Chemical Catg. Silver Sulfate (10294-26-5) No No No Silver compo ------\Federal, State & International Regulations - Part 2\-------RCRA- -TSCA-Ingredient CERCLA 261.33 8(d) Silver Sulfate (10294-26-5) No No No Chemical Weapons Convention: No TSCA 12(b): No CDTA: No

14. Transport Information

SARA 311/312: Acute: Yes Chronic: No Fire: No Pressure: No

Reactivity: No (Pure / Solid) Australian Hazchem Code: None allocated. Poison Schedule: None allocated. WHMIS: This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CH5, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SILVER SULPHATE LR

16. Other Information

NFPA Ratings: Health: 1 Flammability: 0 Reactivity: 1 Label Hazard Warning: WARNING! HARMFUL IF SWALLOWED. Label Precautions: Wash thoroughly after handling. Label First Aid: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Product Use: Laboratory Reagent.

In accordance with REACH Regulation (CE) Nº 1907/2006 and with CLP Regulation (CE) Nº 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This
 document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document