

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SODIUM METABISULPHITE LR

1. Product Identification

Synonyms; Sodium acid sulfite: Sulfurous acid, monosodium salt; Sodium hydrogen sulfite, solid

CAS No.: 7681-57-4

Product Coad: S0189200500

Molecular Weight: 104.06

Chemical Formula: A mixture of NaHSO3 (sodium bisulfite) and Na2S2O5 (sodium metabisulfite)

2. Composition/Information on Ingredients

Ingredient CAS No Percent Hazardous

Sodium Bisulfite 7631-90-5 58 - 99% Yes

Sodium Metabisulfite 7681-57-4 1 - 42% Yes

3. Hazards Identification

Emergency Overview WARNING! HARMFUL IF SWALLOWED OR INHALED. MAY CAUSE ALLERGIC RESPIRATORY REACTION. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. REACTS WITH ACIDS AND WATER RELEASING TOXIC SULFUR DIOXIDE GAS. Inhalation: Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. May cause allergic reaction in sensitive

individuals.

Ingestion: May cause gastric irritation by the liberation of sulfurous acid. An asthmatic reaction may occur after ingestion. Large doses may result in nausea, vomiting, diarrhea, abdominal pains, circulatory disturbance, and central nervous system depression. Estimated fatal dose is 10 gm.

Skin Contact: Causes irritation to skin. Symptoms include redness, itching, and pain.

Eye Contact: Causes irritation, redness, and pain. Contact may cause irreversible eye damage. Symptoms may include stinging, tearing, redness,

Eye Contact: Causes irritation, redness, and pain. Contact may cause irreversible eye damage. Symptoms may include stinging, tearing, redness swelling, corneal damage and blindness.

Chronic Exposure: No information found.

Aggravation of Pre-existing Conditions: Some individuals are said to be dangerously sensitive to minute amounts of sulfites in foods. Symptoms may include broncho constriction, shock, gastrointestinal disturbances, angio edema, flushing, and tingling sensations. Once allergy develops, future exposures can cause asthma attacks with shortness of breath, wheezing, and cough.

4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact: Wipe off excess material from skin then immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard.

Explosion: Not considered to be an explosion hazard.

Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire. Do not allow waterrunoff to enter sewers or waterways. **Special Information:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust. Cautiously spray residue with plenty of water, providing ventilation to clear sulfur dioxide fumes generated from water contact. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Keep in a tightly closed container. Protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. Releases toxic sulfur dioxide gas when in contact with water, ice. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SODIUM METABISULPHITE LR

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-ACGIH Threshold Limit Value (TLV):

5mg/m3 (TWA) for sodium bisulfite & for sodium metabisulfite, A4 Not classifiable as a human carcinogen.

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. Personal Respirators (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half-face respirator with an acid gas cartridge may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece respirator with an acid gas cartridge may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Eye Protection: Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: Coarse white granules. **Odor:** Slight odor of sulfur dioxide.

Solubility: Very soluble in water, insoluble in alcohol.

Specific Gravity: 1.48

pH:

10. Stability and Reactivity

Stability: Strength diminishes somewhat with age. Gradually decomposes in air to sulfate, generating sulfurous acid gas. Contact with moisture (water, wet ice, etc.), will release toxic sulfur dioxide gas.

Hazardous Decomposition Products: Burning may produce sulfur oxides.

Hazardous Polymerization: Will not occur.

Incompatibilities: Water, acids, alkalis, sodium nitrite, oxidizers, aluminum powder. Conditions to Avoid: Moisture, heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Sodium Metabisulfite [7681-57-4]: No LD50/LC50 information found relating to normal routes of occupational exposure. Investigated as a tumorigen, mutagen and reproductive effector. Sodium Bisulfite [7631-90-5]: Oral rat LD50: 2000 mg/kg. Investigated as a tumorigen and mutagen.

NTP Carcinogen				
Ingredient	Known	Anticip	ated	IARC Category
Sodium Bisulfite (7631-90-5	5)	No	No	3
Sodium Metabisulfite (7681	-57-4)	No	No	3

12. Ecological Information

Environmental Fate: No information found. **Environmental Toxicity:** No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SODIUM METABISULPHITE LR

14. Transport Information

Not regulated.

15. Regulatory Information

16. Other Information

NFPA Ratings: Health: 1 Flammability: 0 Reactivity: 1

Label Hazard Warning: WARNING! HARMFUL IF SWALLOWED OR INHALED. MAY CAUSE ALLERGIC RESPIRATORY REACTION. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. REACTS WITH ACIDS AND WATER RELEASING TOXIC SULFUR DIOXIDE GAS.

Label Precautions: Avoid breathing dust. Avoid contact with eyes, skin and clothing.

Keep container closed. Use only with adequate ventilation.

Wash thoroughly after handling. For Reagent and Technical Grades: Not For Food Use. For TAC Grades: Do not use in meats or in foods recognized as a source of Vitamin B-1, nor in fruits or vegetables to be served or sold raw to consumers or to be presented to consumers as fresh.

Label First Aid: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, wipe off excess material from skin then immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention. **Product Use:** Laboratory Reagent.

In accordance with REACH Regulation (CE) No 1907/2006 and with CLP Regulation (CE) No 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document