

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SODIUM OXALATE AR

1. Product Identification

Synonyms: Ethandioic acid disodium salt; disodium salt oxalic acid
CAS No.: 62-76-0

Product Coad: S0190505000

Molecular Weight: 134.00
Chemical Formula: NaOCOCONa

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Sodium Oxalate	62-76-0	99 - 100%	Yes

3. Hazards Identification

Emergency Overview POISON! DANGER! CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY AFFECT KIDNEYS.

Inhalation: Inhalation of dust is corrosive to mucous membranes. Oxalates can be absorbed through the lungs. Symptoms of poisoning include nervousness, cramps, central nervous system depression.

Ingestion: Mean lethal dose for oxalates in adults is estimated at 15-30 grams with death within a few hours or even minutes. Corrosive action on the mucosa and severe gastroenteritis can occur with pain, vomiting, etc. Sharp reduction of serum calcium can cause disfunction of the brain. Calcium oxalate may be deposited in the kidneys. **Skin Contact:** Corrosive. Symptoms of redness, pain, and severe burn can occur. **Eye Contact:** Corrosive. Contact can cause blurred vision, redness, pain and severe tissue burns.

Chronic Exposure: Circulatory failure or nervous system irregularities may follow prolonged calcium metabolism disturbances due to oxalation.

Aggravation of Pre-existing Conditions: Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion: If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard.

Explosion: Not considered to be an explosion hazard.

Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire.

Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: None established.

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SODIUM OXALATE AR

ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved): For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH type N95 or better filters) may be worn. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-face positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear protective gloves and clean body-covering clothing.

Eye Protection: Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: White powder. **Odor:** Odorless. **Solubility:** 3.7g/100g water @ 20C (68F). **Specific Gravity:** 2.34 **pH:** Aqueous solution is neutral. % **Volatiles by volume @ 21C (70F):** 0

10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products: May produce acrid smoke and irritating fumes when heated to decomposition. **Hazardous Polymerization:** Will not occur.

Incompatibilities: Strong oxidizers and strong acids. **Conditions to Avoid:** Heat, incompatibles.

11. Toxicological Information

No LD50/LC50 information found relating to normal routes of occupational exposure.

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category
Sodium Oxalate (62-76-0)	No	No	None

12. Ecological Information

Environmental Fate: No information found.

Environmental Toxicity: No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: TOXIC SOLID, CORROSIVE, ORGANIC, N.O.S. (SODIUM OXALATE)

Hazard Class: 6.1, 8

UN/NA: UN2928

Packing Group: II

International (Water, I.M.O.)

Proper Shipping Name: TOXIC SOLID, CORROSIVE, ORGANIC, N.O.S. (SODIUM OXALATE)

Hazard Class: 6.1, 8

UN/NA: UN2928

Packing Group: II

International (Air, I.C.A.O.)

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

SODIUM OXALATE AR

Proper Shipping Name: TOXIC SOLID, ORGANIC, N.O.S. (SODIUM OXALATE)

Hazard Class: 6.1

UN/NA: UN2811

Packing Group: III

15. Regulatory Information

-----\Chemical Inventory Status - Part 1\-----

Ingredient	TSCA	EC	Japan	Australia
Sodium Oxalate (62-76-0)	Yes	Yes	Yes	Yes

-----\Chemical Inventory Status - Part 2\-----

--Canada--

Ingredient	Korea	DSL	NDSL	Phil.
Sodium Oxalate (62-76-0)	Yes	Yes	No	Yes

-----\Federal, State & International Regulations - Part 1\-----

-SARA 302- -----SARA 313-----

Ingredient	RQ	TPQ	List	Chemical Catg.
Sodium Oxalate (62-76-0)	No	No	No	No

-----\Federal, State & International Regulations - Part 2\-----

-RCRA- -TSCA-

Ingredient	CERCLA	261.33	8(d)
Sodium Oxalate (62-76-0)	No	No	No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No

SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No

Reactivity: No (Pure / Solid)

Australian Hazchem Code: None allocated.

Poison Schedule: None allocated.

WHMIS: This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: **3** Flammability: **0** Reactivity: **0**

Label Hazard Warning: POISON! DANGER! CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY AFFECT KIDNEYS.

Label Precautions: Do not get in eyes, on skin, or on clothing.

Avoid breathing dust.Keep container closed.

Use with adequate ventilation.Wash thoroughly after handling.

Label First Aid: If swallowed, give large quantities of water to drink and call a physician immediately. Never give anything by mouth to an unconscious person. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In all cases get

MATERIAL SAFETY DATA SHEET (MSDS)

SODIUM OXALATE AR

medical attention immediately.

Product Use: Laboratory Reagent.

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document