

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

STRONTIUM CARBONATE LR

1. Product Identification

Synonyms: Carbonic acid, strontium salt (1:1)

CAS No.: 1633-05-2

Product Coad: S0197200500

Molecular Weight: 148 Chemical Formula: SrCO3

2. Composition/Information on Ingredients

Ingredient CAS No Percent Hazardous

Strontium Carbonate 1633-05-2 100% Yes

3. Hazards Identification

Emergency Overview As part of good industrial and personal hygiene and safety procedure, avoid all unnecessary exposure to the chemical substance and ensure prompt removal from skin, eyes and clothing. Inhalation: Nuisance dust. May cause coughing or sneezing if inhaled in large amounts. Excessive inhalation of dust may be irritating to the respiratory tract.

Ingestion: Large oral dosages may produce gastrointestinal disturbances. Substance has low toxicity but ingestion of large amounts of any carbon dioxide-releasing material may cause discomfort, gas and possibly nausea. Skin Contact: No adverse effects expected but dust may cause mechanical irritation.

4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. **Ingestion:** If large amounts were swallowed, give water to drink and get medical advice. **Skin Contact:** Wash exposed area with soap and water. Get medical advice if irritation develops. **Eye Contact:** Wash thoroughly with running water. Get medical advice if irritation develops.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard. Explosion: Not considered to be an explosion hazard.

Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire.

Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from acids and alkalis. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: - OSHA Permissible Exposure Limit (PEL):15 mg/m3 total dust, 5 mg/m3 respirable fraction for nuisance dusts.- ACGIH Threshold Limit Value (TLV):10 mg/m3 total dust containing no asbestos and < 1% crystalline silica for Particulates Not Otherwise Classified (PNOC). Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. Personal Respirators (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present,



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

STRONTIUM CARBONATE LR

use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, airsupplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. Skin Protection: Wear protective gloves and clean body-covering clothing. Eye Protection: Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: White powder. Odor: Odorless.

Solubility: Negligible. Density: 3.5 at 68F (20C) Melting Point: 1100C (2012F)

10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products: May produce oxides of carbon and the contained metal.

Hazardous Polymerization: This substance does not polymerize.

Incompatibilities: Acids.

11. Toxicological Information

No LD50/LC50 information found relating to normal routes of occupational exposure.

---NTP Carcinogen---

Ingredient Known Anticipated IARC Category

Strontium Carbonate (1633-05-2) No No None

12. Ecological Information

Environmental Fate: No information found. Environmental Toxicity: No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

NON HAZARDOUS FOR AIR, ROAD AND SEA TRANSPORT

15. REGULATORY

SARA Title III: N/A Federal Regulatory: N/A

16. Other Information

NFPA Ratings: Health: 0 Flammability: 0 Reactivity: 0

Label Hazard Warning:

As part of good industrial and personal hygiene and safety procedure, avoid all unnecessary exposure to the chemical substance and ensure prompt

removal from skin, eyes and clothing.

Label Precautions: None. Label First Aid: Not applicable. Product Use: Laboratory Reagent.



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAŁ 400062, MH, INDIA.

CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

STRONTIUM CARBONATE LR

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation
 as to its comprehensiveness or accuracy. This document is intended only as a guide to the
 appropriate precautionary handling of the material by a properly trained person using this
 product.

End of document