

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### CARBOL XYLENE (FOR MICROSCOPY)

#### 1. Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Trade name : CARBOL XYLENE (FOR MICROSCOPY)

Product code : SI0302300500

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

##### 1.3. Details of the supplier of the safety data sheet

Company identification SUVCHEM  
 Chaitanya Tower, 2nd Floor, Office # 206,  
 Siddharth Nagar, S.V. Road,  
 Goregaon (West), Mumbai - 400062,  
 Maharashtra, India.  
 Contact: +91 22 28725393 / 94 / 95  
 Email ID: info@suvchem.com/care@suvchem.com

##### 1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [ Office hours ]

#### 2. Hazards identification -DSD

##### 2.1. Classification of the substance or mixture

##### Classification EC 67/548 or EC 1999/45

Not classified.

##### Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Germ cell mutagenicity - Category 2 - Warning (CLP : Muta. 2) H341  
 Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation -  
 Category 3 - Warning (CLP : STOT SE 3) H335  
 Specific Target Organ Toxicity - Repeated exposure - Category 2 - Warning (CLP :  
 STOT RE 2) H373  
 Acute toxicity, dermal - Category 3 - Danger (CLP : Acute Tox. 3) H311  
 Skin corrosion - Category 1B - Danger (CLP : Skin Corr. 1B) H314  
 Acute toxicity, Oral - Category 4 - Warning (CLP : Acute Tox. 4) H302

##### 2.2. Label elements

##### Labelling EC 67/548 or EC 1999/45

Not classified.

**MATERIAL SAFETY DATA SHEET (MSDS)**
**CARBOL XYLENE (FOR MICROSCOPY)**
**2. Hazards identification -DSD (continued)**

**Contains** : Xylene - Phenol

**Labelling Regulation EC 1272/2008 (CLP)**
**Hazard pictograms**


**Signal words** : Danger

**Hazard statements** : H314 : Causes severe skin burns and eye damage.  
 H311 : Toxic in contact with skin.  
 H341 : Suspected of causing genetic defects.  
 H302 : Harmful if swallowed.  
 H335 : May cause respiratory irritation.  
 H373 : May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

- **General** : P201: Obtain special instructions before use.
  - **Prevention** : P280: Wear protective gloves, protective clothing, eye protection, face protection.  
 P271: Use only outdoors or in a well-ventilated area.  
 P260: Do not breathe dust, fume, gas, mist, vapours, spray.  
 P264: Wash thoroughly after handling.  
 P270: Do not eat, drink or smoke when using this product.
  - **Response** : P302+P352: IF ON SKIN : Wash with plenty of soap and water.  
 P301+P330+P331: IF SWALLOWED : Rinse mouth. Do NOT induce vomiting.  
 P308+P313: If exposed or concerned : get medical advice.  
 P305+P351+P338: IF IN EYES : Rinse cautiously with water for several minutes.  
 Remove contact lenses, if present and easy to do. Continue rinsing.  
 P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing.  
 P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminated clothing. Rinse skin with water/shower.  
 P363: Wash contaminated clothing before reuse.  
 P314: Get medical advice if you feel unwell.  
 P361: Remove immediately all contaminated clothing.
  - **Storage** : P403+P233: Store in well-ventilated place. Keep container tightly closed.  
 P405: Store locked up.
  - **Disposal considerations** : P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- Contains** : Xylene - Phenol

**2.3. Other hazards**

**Other hazards** : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### CARBOL XYLENE (FOR MICROSCOPY)

#### 3. Composition/information on ingredients

Substance / Preparation		: Preparation.					
Substance name		Contents	CAS No	EC No	Annex No	REACH Ref.	Classification
Xylene	:	> 75 < 99 %	1330-20-7	215-535-7	601-022-00-9	----	R10 Xn; R20/21 Xi; R38 ----- Flam. Liq. 3 _ H226 Acute Tox. 4 (skin) _ H312 Acute Tox. 4 (inhal) _ H332 Skin Irrit. 2 _ H315 STOT SE 3 _ H335
Phenol	:	> 25 < 50 %	108-95-2	203-632-7	604-001-00-2	----	Muta. Cat. 3; R68 T; R23/24/25 Xn; R48/20/21/22 C; R34 ----- Acute Tox. 3 (skin) _ H311 Acute Tox. 3 (inhal) _ H331 Acute Tox. 3 (oral) _ H301 Skin Corr. 1B _ H314 Eye Dam 1 _ H318 Muta. 2 _ H341 STOT RE 2 _ H373

#### 4. First aid measures

##### 4.1. Description of first aid measures

Inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor. Call a POISON CENTER or doctor if you feel unwell.
Skin contact	: Specific treatment (see on this label). Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Wash with plenty of soap and water. Immediately call a POISON CENTER or doctor.
Eye contact	: Immediately call a POISON CENTER or doctor. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.
Ingestion	: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

##### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Swallowing a small quantity of this material will result in serious health hazard. Suspected of causing genetic defects. Causes damage to organ. Causes severe skin burns and eye damage. May cause respiratory irritation.
--------------------------	---

##### 4.3. Indication of any immediate medical attention and special treatment needed

General information	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
---------------------	---

#### 5. Fire-fighting measures

##### 5.1. Extinguishing media

**MATERIAL SAFETY DATA SHEET (MSDS)**
**CARBOL XYLENE (FOR MICROSCOPY)**
**5. Fire-fighting measures (continued)**

<b>Suitable extinguishing media</b>	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
<b>Unsuitable extinguishing media</b>	: Do not use a heavy water stream.
<b>Surrounding fires</b>	: Use water spray or fog for cooling exposed containers.

**5.2. Special hazards arising from the substance or mixture**

<b>Hazardous combustion products</b>	: Under fire conditions, hazardous fumes will be present. Thermal decomposition generates : Corrosive vapours.
--------------------------------------	---

**5.3. Advice for fire-fighters**

<b>Protection against fire</b>	: Do not enter fire area without proper protective equipment, including respiratory protection.
<b>Special procedures</b>	: Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

**6. Accidental release measures**
**6.1. Personal precautions, protective equipment and emergency procedures**

<b>For emergency responders</b>	: Equip cleanup crew with proper protection. Ventilate area.
<b>For non-emergency personnel</b>	: Evacuate unnecessary personnel.

**6.2. Environmental precautions**

<b>Environmental precautions</b>	: Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.
----------------------------------	--

**6.3. Methods and material for containment and cleaning up**

<b>Clean up methods</b>	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

**6.4. Reference to other sections**

See section 8. Exposure controls/personal protection

**7. Handling and storage**
**7.1. Precautions for safe handling**

<b>Handling</b>	: Do not breathe dust, fume, gas, mist, vapours, spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Wash contaminated clothing before reuse. Wash thoroughly after handling. Use personal protective equipment as required. Do not eat, drink or smoke when using this product.
-----------------	---

**MATERIAL SAFETY DATA SHEET (MSDS)**
**CARBOL XYLENE (FOR MICROSCOPY)**
**7. Handling and storage (continued)**

- Technical protective measures** : Provide good ventilation in process area to prevent formation of vapour.  
**Special precautions** : Avoid breathing dust, fume, gas, mist, vapours, spray.

**7.2. Conditions for safe storage, including any incompatibilities**

- Storage** : Keep only in the original container in a cool, well ventilated place. Keep container tightly closed.  
**Storage regulation** : Comply with applicable regulations.  
**Storage - away from** : Strong bases. Strong acids. Sources of ignition. Direct sunlight.

**7.3. Specific end use(s)**

- Specific end use(s)** : None.

**8. Exposure controls/personal protection**
**8.1. Exposure controls**
**Personal protection**


- Personal protection** : Avoid all unnecessary exposure.  
**• Respiratory protection** : Wear approved mask.  
**• Hand protection** : Wear protective gloves.  
**• Skin protection** : Wear suitable protective clothing.  
**• Eye protection** : Chemical goggles or face shield.  
**• Others** : When using, do not eat, drink or smoke.

**8.2. Control parameters**

- Occupational Exposure Limits** : No data available.  
**Occupational Exposure Limits** : Xylene : ILV (EU) - 8 H - [mg/m<sup>3</sup>] : ( 221 Skin. )  
 Xylene : ILV (EU) - 8 H - [ppm] : ( 50 Skin. )  
 Xylene : ILV (EU) - 15 min - [mg/m<sup>3</sup>] : ( 442 Skin. )  
 Xylene : ILV (EU) - 15 min - [ppm] : ( 100 Skin. )  
 Xylene : HTP-värden - 8 H - [ppm] : 50  
 Xylene : HTP-värden - 15min - [ppm] : 100  
 Xylene : HTP-värden - 8 H - [mg/m<sup>3</sup>] : 220  
 Xylene : HTP-värden - 15min - [mg/m<sup>3</sup>] : 440  
 Xylene : NGV - [ppm] : 50  
 Xylene : NGV - [mg/m<sup>3</sup>] : 200  
 Xylene : KTV - [ppm] : 100  
 Xylene : KTV - [mg/m<sup>3</sup>] : 450  
 Xylene : VLA-ED [ppm] : 50  
 Xylene : VLA-ED [mg/m<sup>3</sup>] : 221  
 Xylene : VLA-EC [ppm] : 100

**MATERIAL SAFETY DATA SHEET (MSDS)**
**CARBOL XYLENE (FOR MICROSCOPY)**
**8. Exposure controls/personal protection (continued)**

 Xylene : VLA-EC [mg/m<sup>3</sup>] : 442

**9. Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Physical state at 20 °C	: Liquid.
Colour	: Clear Colorless
Odour	: Aromatic odor
Odour threshold	: No data available.
pH value	: No data available.
Melting point [°C]	: -47.4 deg C
Decomposition point [°C]	: N/A
Critical temperature [°C]	: N/A
Auto-ignition temperature [°C]	: 527 deg C
Flammability (solid, gas)	: N/A
Flash point [°C]	: 32 deg C
Boiling point [°C]	: 138.3 deg C
Initial boiling point [°C]	: N/A
Final boiling point [°C]	: N/A
Evaporation rate	: N/A
Vapour pressure [20°C]	: 6.72 mm Hg
Vapour pressure mm/Hg	: N/A
Vapour density	: N/A
Density [g/cm <sup>3</sup> ]	: N/A
Relative density, gas (air=1)	: N/A
Relative density, liquid (water=1)	: N/A
Solubility in water [% weight]	: N/A
Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: Insoluble in water, soluble in alcohol
Viscosity at 40°C [mm <sup>2</sup> /s]	: N/A

**9.2. Other information**

Explosive properties	: N/A
Explosion limits - upper [%]	: N/A
Explosion limits - lower [%]	: N/A
Oxidising properties	: No data available.

**MATERIAL SAFETY DATA SHEET (MSDS)**
**CARBOL XYLENE (FOR MICROSCOPY)**
**10. Stability and reactivity**
**10.1. Reactivity**

Reactivity : Not established.

**10.2. Chemical stability**

Chemical stability : Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

Hazardous reactions : Not established.

**10.4. Conditions to avoid**

Conditions to avoid : Direct sunlight. Extremely high or low temperatures.

**10.5. Incompatible materials**

Materials to avoid : Strong acids. Strong bases.

**10.6. Hazardous decomposition products**

 Hazardous decomposition products : Fumes. Carbon monoxide. Carbon dioxide.  
 Thermal decomposition generates : Corrosive vapours.

**11. Toxicological information**
**11.1. Information on toxicological effects**

Toxicity information : The product has been not fully tested. The calculated risk has been done under the requirements of the EU regulations.

 Acute toxicity : LD50/LC50:  
 CAS# 108-95-2: Draize test, rabbit, eye: 5 mg Severe; Draize test, rabbit, skin: 500 mg/24H Severe; Draize test, rabbit, skin: 100mg Mild; Inhalation, mouse: LC50 = 177 mg/m<sup>3</sup>; Inhalation, mouse: LC50, 177 mg/m<sup>3</sup>/4H; Inhalation, rat: LC50 = 316 mg/m<sup>3</sup>; Inhalation, rat: LC50 = 316 mg/m<sup>3</sup>/4H; Oral, mouse: LD50 = 270 mg/kg; Oral, rat: LD50 = 317 mg/kg; Oral, rat: LD50 = 512 mg/kg; Skin, rabbit: LD50 = 630mg/kg; Skin, rat: LD50 = 669 mg/kg; Skin, rat: LD50 = 1500 mg/kg.

• Inhalation : Based on available data, the classification criteria are not met.

• Dermal : Toxic in contact with skin.

• Ingestion : Harmful if swallowed.

Corrosion : Causes severe skin burns and eye damage.

Irritation : May cause respiratory irritation.

Sensitization : Based on available data, the classification criteria are not met.

Mutagenicity : Suspected of causing genetic defects.



**MATERIAL SAFETY DATA SHEET (MSDS)**
**CARBOL XYLENE (FOR MICROSCOPY)**
**11. Toxicological information (continued)**

<b>Carcinogenicity</b>	: Based on available data, the classification criteria are not met.
<b>Toxic for reproduction</b>	: Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	: Based on available data, the classification criteria are not met.
<b>STOT-repeated exposure</b>	: May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	: Based on available data, the classification criteria are not met.

**12. Ecological information**
**12.1. Toxicity**

<b>Toxicity information</b>	: The product has been not fully tested. The calculated risk has been done under the requirements of the EU regulations.
-----------------------------	--

**12.2. Persistence - degradability**

<b>Persistence - degradability</b>	: Biodegradable.
------------------------------------	------------------

**12.3. Bioaccumulative potential**

<b>Bioaccumulative potential</b>	: Not established.
----------------------------------	--------------------

**12.4. Mobility in soil**

<b>Mobility in soil</b>	: Not established.
-------------------------	--------------------

**12.5. Results of PBT and vPvB assessment**

<b>Results of PBT and vPvB assessment</b>	: The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.
---	---

**12.6. Other adverse effects**

<b>Environmental precautions</b>	: Avoid release to the environment.
----------------------------------	-------------------------------------

**13. Disposal considerations**
**13.1. Waste treatment methods**

<b>General</b>	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
<b>Special precautions</b>	: Hazardous waste due to toxicity.



**MATERIAL SAFETY DATA SHEET (MSDS)**
**CARBOL XYLENE (FOR MICROSCOPY)**
**14. Transport information**
**14.1. Land transport (ADR-RID)**

Proper shipping name : XYLENES  
 UN N° : 1307  
 H.I. nr : 30  
 ADR - Class : 3  
 Labelling - Transport : 3 : Flammable liquid.



ADR - Classification code : F1  
 ADR - Group : III  
 ADR - Packing instructions : P001 R001 LP001  
 ADR - Limited Quantity : 5 L  
 ADR - Tunnel code



: D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and  
 E. Other carriage: Passage forbidden through tunnels of category E.

**14.2. Sea transport (IMDG) [English only]**

Proper shipping name : XYLENES  
 UN N° : 1307  
 IMO-IMDG - Class or division : 3 : Flammable liquid.  
 IMO-IMDG - Packing group : III  
 IMO-IMDG - Packing instructions : P001 LP01  
 IMO-IMDG - Limited quantities : 5 L  
 IMO-IMDG - Marine pollution : No  
 EMS-Nr : F-E S-D

**14.3. Air transport (ICAO-IATA) [English only]**

Proper shipping name : XYLENES  
 UN N° : 1307  
 IATA - Class or division : 3 : Flammable liquid.  
 IATA - Packing group : III  
 IATA - Passenger and Cargo Aircraft : ALLOWED  
 - Passenger and Cargo - Packing instruction : 355

**MATERIAL SAFETY DATA SHEET (MSDS)**
**CARBOL XYLENE (FOR MICROSCOPY)**
**14. Transport information (continued)**

- Passenger and Cargo - Maximum	: 60 L
Quantity/Packing	
IATA - Cargo only	: ALLOWED
- Cargo only - Packing instruction	: 366
- Cargo only - Maximum Quantity/	: 220 L
Packing	
IATA - Limited Quantities	: 10 L
ERG-Nr	: 3L

**15. Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Safety, health and environmental regulations/legislation specific for the substance or mixture	: Ensure all national/local regulations are observed.
REACH Restrictions - Annex XVII	: The components of this product are not subject to restrictions.
REACH Authorisation - Annex XIV	: The components of this product are not subject to authorization.

**15.2. Chemical Safety Assessment**

Chemical Safety Assessment	: It has not been carried out.
----------------------------	--------------------------------

**16. Other information**

Revision	: Revision - See : *
Abbreviations and acronyms	: PBT: persistent, bioaccumulative and toxic. vPvB: very persistent and very bioaccumulative
Sources of key data used	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
List of relevant R phrases (heading 3)	: R10 : Flammable. R20/21 : Harmful by inhalation and in contact with skin. R23/24/25 : Toxic by inhalation, in contact with skin and if swallowed. R34 : Causes burns. R38 : Irritating to skin. R48/20/21/22 : Harmful : danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. R68 : Possible risks of irreversible effects.
List of full text of H-statements in section 3	: H226 : Flammable liquid and vapour. H301 : Toxic if swallowed. H311 : Toxic in contact with skin. H312 : Harmful in contact with skin. H314 : Causes severe skin burns and eye damage. H315 : Causes skin irritation. H318 : Causes serious eye damage.

## MATERIAL SAFETY DATA SHEET (MSDS)

### CARBOL XYLENE (FOR MICROSCOPY)

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

#### DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document