

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### TOLUENE RECTIFIED LR

#### 1. Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Trade name : TOLUENE RECTIFIED LR

Product code : SS0105100500

Identification of the product : Toluene  
 CAS No: 108-88-3  
 EC No :203-625-9  
 Annex No :601-021-00-3

Chemical formula : C<sub>7</sub>H<sub>8</sub> - (C(CH<sub>3</sub>)CHCHCHCHCH)

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

##### 1.3. Details of the supplier of the safety data sheet

Company identification SUVCHEM  
 Chaitanya Tower, 2nd Floor, Office # 206,  
 Siddharth Nagar, S.V. Road,  
 Goregaon (West), Mumbai - 400062,  
 Maharashtra, India.  
 Contact: +91 22 28725393 / 94 / 95  
 Email ID: info@suvchem.com/care@suvchem.com

##### 1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [ Office hours ]

#### 2. Hazards identification -DSD

##### 2.1. Classification of the substance or mixture

##### Classification EC 67/548 or EC 1999/45

Classification : F; R11  
 Repr. Cat. 3; R63  
 Xn; R65-48/20  
 R67  
 Xi; R38

##### Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Reproductive toxicity - Unborn Child - Category 2 - Warning (CLP : Repr. 2) H361  
 Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation -  
 Category 3 - Warning (CLP : STOT SE 3) H335  
 Specific Target Organ Toxicity - Single exposure - Narcotic effects - Category 3 -  
 Warning (CLP : STOT SE 3) H336

**MATERIAL SAFETY DATA SHEET (MSDS)**
**TOLUENE RECTIFIED LR**
**2. Hazards identification -DSD (continued)**

Physical hazards : Specific Target Organ Toxicity - Repeated exposure - Category 2 - Warning (CLP : STOT RE 2) H373  
 Aspiration hazard - Category 1 - Danger (CLP : Asp. Tox. 1) H304  
 Skin irritation - Category 2 - Warning (CLP : Skin Corr. 2) H315  
 : Flammable liquids - Category 2 - Danger (CLP : Flam. Liq. 2) H225

**2.2. Label elements**
**Labelling EC 67/548 or EC 1999/45**
**Symbol(s)**

**Symbol(s)**

: F : Highly flammable  
 Xn : Harmful

**R Phrase(s)**

: R11 : Highly flammable.  
 R38 : Irritating to skin.  
 R48/20 : Harmful : danger of serious damage to health by prolonged exposure through inhalation.  
 R63 : Possible risk of harm to the unborn child.  
 R65 : Harmful : may cause lung damage if swallowed.  
 R67 : Vapours may cause drowsiness and dizziness.

**S Phrase(s)**

: S2 : Keep out of the reach of children.  
 S36/37 : Wear suitable protective clothing and gloves.  
 S62 : If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label.

**Contains**

: Toluene

**Labelling Regulation EC 1272/2008 (CLP)**
**Hazard pictograms**

**Signal words**

: Danger

**Hazard statements**

: H225 : Highly flammable liquid and vapour.  
 H304 : May be fatal if swallowed and enters airways.  
 H315 : Causes skin irritation.  
 H335 : May cause respiratory irritation.  
 H336 : May cause drowsiness or dizziness.  
 H373 : May cause damage to organs through prolonged or repeated exposure.  
 H361d: Suspected of damaging the unborn child.

**Precautionary statements**

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### TOLUENE RECTIFIED LR

#### 2. Hazards identification -DSD (continued)

- **General** : P102: Keep out of reach of children.  
 P103: Read label before use.  
 P101: If medical advice is needed, have product container or label at hand.  
 P201: Obtain special instructions before use.
- **Prevention** : P240: Ground/bond container and receiving equipment.  
 P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment.  
 P210: Keep away from heat, sparks, open flames or hot surfaces. - No smoking.  
 P280: Wear protective gloves, protective clothing, eye protection, face protection.  
 P271: Use only outdoors or in a well-ventilated area.  
 P260: Do not breathe dust, fume, gas, mist, vapours, spray.  
 P233: Keep container tightly closed.  
 P264: Wash thoroughly after handling.
- **Response** : P301+P310: IF SWALLOWED : Immediately call a POISON CENTER or doctor.  
 P302+P352: IF ON SKIN : Wash with plenty of soap and water.  
 P308+P313: If exposed or concerned : get medical advice.  
 P332+P313: If skin irritation occurs : Get medical advice.  
 P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing.  
 P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminated clothing. Rinse skin with water/shower.  
 P363: Wash contaminated clothing before reuse.  
 P314: Get medical advice if you feel unwell.  
 P370+P378: In case of fire: Use for extinction.
- **Storage** : P403+P233: Store in well-ventilated place. Keep container tightly closed.  
 P403+P235: Store in well-ventilated place. Keep cool.  
 P405: Store locked up.
- **Disposal considerations** : P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- Contains** : Toluene

#### 2.3. Other hazards

- Other hazards** : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

#### 3. Composition/information on ingredients

**Substance / Preparation** : Toluene

EC No :203-625-9  
 Annex No :601-021-00-3  
 Substance.

Substance name	Contents	CAS No	EC No	Annex No	REACH Ref.	Classification
Toluene	100 %	108-88-3	203-625-9	601-021-00-3	----	F; R11 Repr. Cat. 3; R63 Xn; R65-48/20 R67 Xi; R38 ----- Flam. Liq. 2 _ H225 Asp. Tox 1 _ H304

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### TOLUENE RECTIFIED LR

#### 3. Composition/information on ingredients (continued)

Repr. 2 \_ H361d  
 Skin Irrit. 2 \_ H315  
 STOT SE 3 \_ H335  
 STOT RE 2 \_ H373  
 STOT SE 3 \_ H336

Contains no other components or impurities which will influence the classification of the product.

#### 4. First aid measures

##### 4.1. Description of first aid measures

Inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
Skin contact	: Wash contaminated clothing before reuse. If skin irritation occurs : Wash with plenty of soap and water. Get medical advice. Specific treatment (see on this label). Remove/Take off immediately all contaminated clothing.
Eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
Ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.

##### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use	: Causes damage to organ. May be fatal if swallowed and enters airways. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child.
--------------------------	---

##### 4.3. Indication of any immediate medical attention and special treatment needed

General information	: Never give anything by mouth to an unconscious person. If exposed or concerned : get medical advice.
---------------------	---

#### 5. Fire-fighting measures

##### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
Surrounding fires	: Use water spray or fog for cooling exposed containers.

##### 5.2. Special hazards arising from the substance or mixture

Flammable class	: Highly flammable liquid and vapour.
Hazardous combustion products	: Under fire conditions, hazardous fumes will be present.

**MATERIAL SAFETY DATA SHEET (MSDS)**
**TOLUENE RECTIFIED LR**
**5. Fire-fighting measures (continued)**
**5.3. Advice for fire-fighters**

- Protection against fire** : Do not enter fire area without proper protective equipment, including respiratory protection.
- Special procedures** : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

**6. Accidental release measures**
**6.1. Personal precautions, protective equipment and emergency procedures**

- For emergency responders** : Equip cleanup crew with proper protection.  
Ventilate area.  
Avoid breathing dust, fume, gas, mist, vapours, spray.
- Technical measures** : Use special care to avoid static electric charges.
- Special precautions** : Remove ignition sources. No naked lights. No smoking.
- For non-emergency personnel** : Evacuate unnecessary personnel.

**6.2. Environmental precautions**

- Environmental precautions** : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

**6.3. Methods and material for containment and cleaning up**

- Clean up methods** : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

**6.4. Reference to other sections**

See section 8. Exposure controls/personal protection

**7. Handling and storage**
**7.1. Precautions for safe handling**

- Handling** : Handle empty containers with care because residual vapours are flammable. Obtain special instructions before use. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.
- Technical protective measures** : Provide good ventilation in process area to prevent formation of vapour. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating, lighting, ..., equipment.

**MATERIAL SAFETY DATA SHEET (MSDS)**
**TOLUENE RECTIFIED LR**
**7. Handling and storage (continued)**

**Special precautions** : No naked lights. No smoking. Avoid breathing dust, fume, gas, mist, vapours, spray.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage** : Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Ground/bond container and receiving equipment. Keep container tightly closed.

**Storage - away from** : Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.

**7.3. Specific end use(s).**

**Specific end use(s)** : None.

**8. Exposure controls/personal protection**
**8.1. Exposure controls**

**Personal protection** : Avoid all unnecessary exposure.

- **Respiratory protection** : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.  
Wear respiratory protection.
- **Hand protection** : Wear protective gloves.
- **Skin protection** : Wear suitable protective clothing.
- **Eye protection** : Chemical goggles or safety glasses.
- **Others** : When using, do not eat, drink or smoke.

**8.2. Control parameters**

**Occupational Exposure Limits** : No data available.

ILV (EU) - 8 H - [ppm] : ( 50 Skin. )

ILV (EU) - 8 H - [mg/m<sup>3</sup>] : ( 192 Skin. )

ILV (EU) - 15 min - [ppm] : ( 100 Skin. )

ILV (EU) - 15 min - [mg/m<sup>3</sup>] : ( 384 Skin. )

OEL (UK)-LTEL [ppm] : 50

OEL (UK)-STEL [ppm] : 150

**9. Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

**Physical state at 20 °C** : Liquid.

**MATERIAL SAFETY DATA SHEET (MSDS)**
**TOLUENE RECTIFIED LR**
**9. Physical and chemical properties (continued)**

Colour	: Clear Colorless
Odour	: Aromatic benzene-like
Odour threshold	: No data available.
pH value	: No data available.
Melting point [°C]	: -95
Decomposition point [°C]	: N/A
Critical temperature [°C]	: N/A
Auto-ignition temperature [°C]	: 535
Flammability (solid, gas)	: Flammable. Highly flammable liquid and vapour.
Flash point [°C]	: 4°C
Boiling point [°C]	: 110 - 111 °C
Initial boiling point [°C]	: 110 °C
Final boiling point [°C]	: 111 °C
Evaporation rate	: 2,24
Vapour pressure [20°C]	: 22 @ 20C
Vapour pressure mm/Hg	: 22 @ 20C
Vapour density	: 3,14
Density [g/cm <sup>3</sup> ]	: 0,86
Relative density, gas (air=1)	: 3.2
Relative density, liquid (water=1)	: N/A
Solubility in water [% weight]	: Insoluble.
Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: N/A
Viscosity at 40°C [mm <sup>2</sup> /s]	: N/A

**9.2. Other information**

Explosive properties	: N/A
Explosion limits - upper [%]	: 7
Explosion limits - lower [%]	: 1.2
Oxidising properties	: No data available.

**10. Stability and reactivity**
**10.1. Reactivity**

Reactivity	: Not established.
------------	--------------------



**MATERIAL SAFETY DATA SHEET (MSDS)**
**TOLUENE RECTIFIED LR**
**10. Stability and reactivity (continued)**
**10.2. Chemical stability**

**Chemical stability** : Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions** : Not established.

**10.4. Conditions to avoid**

**Conditions to avoid** : Direct sunlight. Extremely high or low temperatures. Open flame.

**10.5. Incompatible materials**

**Materials to avoid** : Strong acids. Strong bases.

**10.6. Hazardous decomposition products**

**Hazardous decomposition products** : Fumes. Carbon monoxide. Carbon dioxide.  
May release flammable gases.

**11. Toxicological information**
**11.1. Information on toxicological effects**
**Acute toxicity**

- **Inhalation** : May be fatal if swallowed and enters airways.
- **Dermal** : Based on available data, the classification criteria are not met.
- **Ingestion** : May be fatal if swallowed and enters airways.
- **Rat oral LD50 [mg/kg]** : 7000

**Corrosion**

: Based on available data, the classification criteria are not met.

**Irritation**

: Causes skin irritation.  
May cause respiratory irritation.

**Sensitization**

: Based on available data, the classification criteria are not met.

**Mutagenicity**

: Based on available data, the classification criteria are not met.

**Carcinogenicity**

: Based on available data, the classification criteria are not met.

**Toxic for reproduction**

: Suspected of damaging the unborn child.

**STOT-single exposure**

: May cause drowsiness or dizziness.

**STOT-repeated exposure**

: May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

: May be fatal if swallowed and enters airways.



**MATERIAL SAFETY DATA SHEET (MSDS)**
**TOLUENE RECTIFIED LR**
**12. Ecological information**
**12.1. Toxicity**

Toxicity information : Not established.

**12.2. Persistence - degradability**

Persistence - degradability : Biodegradable.

**12.3. Bioaccumulative potential**

Bioaccumulative potential : Not established.

**12.4. Mobility in soil**

Mobility in soil : Not established.

Log Pow octanol / water at 20°C : 2.6

**12.5. Results of PBT and vPvB assessment**

Results of PBT and vPvB assessment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

**12.6. Other adverse effects**

Environmental precautions : Avoid release to the environment.

**13. Disposal considerations**
**13.1. Waste treatment methods**

**General** : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.  
 Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

**Special precautions** : Handle empty containers with care because residual vapours are flammable.  
 Hazardous waste due to toxicity.

**14. Transport information**
**14.1. Land transport (ADR-RID)**

Proper shipping name : TOLUENE  
 UN N° : 1294

**MATERIAL SAFETY DATA SHEET (MSDS)**
**TOLUENE RECTIFIED LR**
**14. Transport information (continued)**

H.I. nr : 33  
 ADR - Class : 3  
 Labelling - Transport : 3 : Flammable liquid.



ADR - Classification code : F1  
 ADR - Group : II  
 ADR - Packing instructions : P001 R001  
 ADR - Limited Quantity : 1 L  
 ADR - Tunnel code : D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.


**14.2. Sea transport (IMDG) [English only]**

Proper shipping name : TOLUENE  
 UN N° : 1294  
 IMO-IMDG - Class or division : 3 : Flammable liquid.  
 IMO-IMDG - Packing group : II  
 IMO-IMDG - Packing instructions : P001  
 IMO-IMDG - Limited quantities : 1 L  
 IMO-IMDG - Marine pollution : No  
 EMS-Nr : F-E S-D

**14.3. Air transport (ICAO-IATA) [English only]**

Proper shipping name : TOLUENE  
 UN N° : 1294  
 IATA - Class or division : 3 : Flammable liquid.  
 IATA - Packing group : II  
 IATA - Passenger and Cargo Aircraft : ALLOWED  
   - Passenger and Cargo - Packing : 353  
 instruction  
   - Passenger and Cargo - Maximum : 5 L  
 Quantity/Packing  
 IATA - Cargo only : ALLOWED

**MATERIAL SAFETY DATA SHEET (MSDS)**
**TOLUENE RECTIFIED LR**
**14. Transport information (continued)**

- Cargo only - Packing instruction	: 364
- Cargo only - Maximum Quantity/ Packing	: 60 L
IATA - Limited Quantities	: 1 L
ERG-Nr	: 3L

**15. Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Safety, health and environmental regulations/legislation specific for the substance or mixture	: Ensure all national/local regulations are observed.
REACH Restrictions - Annex XVII	: With the exception of those listed below: Annex XVII The components of this product are not subject to restrictions.
REACH Authorisation - Annex XIV	: The components of this product are not subject to authorization.

**15.2. Chemical Safety Assessment**

Chemical Safety Assessment	: It has not been carried out.
----------------------------	--------------------------------

**16. Other information**

Revision	: Revision - See : *
Abbreviations and acronyms	: PBT: persistent, bioaccumulative and toxic. vPvB: very persistent and very bioaccumulative
Sources of key data used	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
List of relevant R phrases (heading 3)	: R11 : Highly flammable. R38 : Irritating to skin. R48/20 : Harmful : danger of serious damage to health by prolonged exposure through inhalation. R63 : Possible risk of harm to the unborn child. R65 : Harmful : may cause lung damage if swallowed. R67 : Vapours may cause drowsiness and dizziness.
List of full text of H-statements in section 3	: H225 : Highly flammable liquid and vapour. H304 : May be fatal if swallowed and enters airways. H315 : Causes skin irritation. H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness. H361U : Suspected of damaging the unborn child. H373 : May cause damage to organs through prolonged or repeated exposure.

**MATERIAL SAFETY DATA SHEET (MSDS)**

**TOLUENE RECTIFIED LR**

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

**DISCLAIMER:**

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

**End of document**