

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
 Product code : SS0109000500
 Identification of the product : 4-Methylpentan-2-one
 CAS No: 108-10-1
 EC No :203-550-1
 Annex No :606-004-00-4
 Chemical formula : C₆H₁₂O

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification : SUVCHEM
 Chaitanya Tower, 2nd Floor, Office # 206,
 Siddharth Nagar, S.V. Road,
 Goregaon (West), Mumbai - 400062,
 Maharashtra, India.
 Contact: +91 22 28725393 / 94 / 95
 Email ID: info@suvchem.com/care@suvchem.com

1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification : F; R11
 Xn; R20
 R66
 Xi; R36/37

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation -
 Category 3 - Warning (CLP : STOT SE 3) H335
 Eye irritation - Category 2A - Warning (CLP : Eye Irrit. 2) H319
 Acute toxicity, Inhalation - Category 4 - Warning (CLP : Acute Tox. 4) H332

MATERIAL SAFETY DATA SHEET (MSDS)
iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
2. Hazards identification -DSD (continued)

Physical hazards : Flammable liquids - Category 2 - Danger (CLP : Flam. Liq. 2) H225

2.2. Label elements
Labelling EC 67/548 or EC 1999/45
Symbol(s)

Symbol(s)

: Xn : Harmful
F : Highly flammable

R Phrase(s)

: R11 : Highly flammable.
R20 : Harmful by inhalation.
R36/37 : Irritating to eyes and respiratory system.
R66 : Repeated exposure may cause skin dryness or cracking.

S Phrase(s)

: S2 : Keep out of the reach of children.
S9 : Keep container in a well-ventilated place.
S16 : Keep away from sources of ignition - No smoking.
S29 : Do not empty into drains.

Contains

: 4-Methylpentan-2-one

Labelling Regulation EC 1272/2008 (CLP)
Hazard pictograms

Signal words

: Danger

Hazard statements

: H225 : Highly flammable liquid and vapour.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.

Precautionary statements
• General

: P102: Keep out of reach of children.
P103: Read label before use.
P101: If medical advice is needed, have product container or label at hand.

• Prevention

: P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment.
P210: Keep away from heat, sparks, open flames or hot surfaces. - No smoking.
P280: Wear protective gloves, protective clothing, eye protection, face protection.
P271: Use only outdoors or in a well-ventilated area.
P261: Avoid breathing dust, fume, gas, mist, vapours, spray.
P233: Keep container tightly closed.
P264: Wash thoroughly after handling.

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)

2. Hazards identification -DSD (continued)

- **Response** : P305+P351+P338: IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing.
 P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminated clothing. Rinse skin with water/shower.
 P337+P313: If eye irritation persists: Get medical advice/attention.
 P370+P378: In case of fire: Use for extinction.
- **Storage** : P403+P233: Store in well-ventilated place. Keep container tightly closed.
 P403+P235: Store in well-ventilated place. Keep cool.
 P405: Store locked up.
- **Disposal considerations** : P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- Contains** : 4-Methylpentan-2-one

2.3. Other hazards

- Other hazards** : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

Substance / Preparation : 4-Methylpentan-2-one

EC No :203-550-1
 Annex No :606-004-00-4
 Substance.

Substance name	Contents	CAS No	EC No	Annex No	REACH Ref.	Classification
4-Methylpentan-2-one	100 %	108-10-1	203-550-1	606-004-00-4	----	F; R11 Xn; R20 R66 Xi; R36/37 ----- Flam. Liq. 2 _ H225 Acute Tox. 4 (inhal) _ H332 Eye irrit 2 _ H319 STOT SE 3 _ H335 STOT RE _ EUH066

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures

4.1. Description of first aid measures

- Inhalation** : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
- Skin contact** : Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing.

MATERIAL SAFETY DATA SHEET (MSDS)
iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
4. First aid measures (continued)

- Eye contact** : Get medical advice. If eye irritation persists : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.
- Ingestion** : Obtain emergency medical attention. Do NOT induce vomiting. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms relating to use** : Danger of serious damage to health by prolonged exposure through inhalation. Causes serious eye irritation. May cause respiratory irritation. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

- General information** : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures
5.1. Extinguishing media

- Suitable extinguishing media** : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media** : Do not use a heavy water stream.
- Surrounding fires** : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

- Flammable class** : Highly flammable liquid and vapour.
- Hazardous combustion products** : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

- Protection against fire** : Do not enter fire area without proper protective equipment, including respiratory protection.
- Special procedures** : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

6. Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures

- For emergency responders** : Equip cleanup crew with proper protection. Ventilate area.
- Technical measures** : Use special care to avoid static electric charges.
- Special precautions** : Remove ignition sources. No naked lights. No smoking.

MATERIAL SAFETY DATA SHEET (MSDS)
iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
6. Accidental release measures (continued)

For non-emergency personnel : Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Store away from other materials. Collect spillage.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage
7.1. Precautions for safe handling

Handling : Handle empty containers with care because residual vapours are flammable. Use only outdoors or in a well-ventilated area.
Wash thoroughly after handling. Avoid breathing dust, fume, gas, mist, vapours, spray.

Technical protective measures : Provide good ventilation in process area to prevent formation of vapour. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating, lighting, ..., equipment.

Special precautions : No naked lights. No smoking. Avoid breathing dust, fume, gas, mist, vapours, spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Keep container tightly closed. Ground/bond container and receiving equipment.

Storage - away from : Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Specific end use(s) : None.

8. Exposure controls/personal protection
8.1. Exposure controls

MATERIAL SAFETY DATA SHEET (MSDS)
iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
8. Exposure controls/personal protection (continued)

Personal protection	: Avoid all unnecessary exposure.
• Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.
• Hand protection	: Wear protective gloves.
• Eye protection	: Chemical goggles or safety glasses.
• Others	: When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits	: No data available.
OEL (UK)-LTEL [ppm]	: 50
OEL (UK)-STEL [ppm]	: 100

9. Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state at 20 °C	: Liquid.
Colour	: Clear Colorless
Odour	: Slight camphor odor
Odour threshold	: No data available.
pH value	: No data available.
Melting point [°C]	: -80
Decomposition point [°C]	: N/A
Critical temperature [°C]	: N/A
Auto-ignition temperature [°C]	: 475
Flammability (solid, gas)	: Flammable. Highly flammable liquid and vapour.
Flash point [°C]	: 14
Boiling point [°C]	: 116
Initial boiling point [°C]	: 117°C
Final boiling point [°C]	: 118 °C
Evaporation rate	: N/A
Vapour pressure [20°C]	: 20 hPa at 20 °C
Vapour pressure mm/Hg	: 5.3 (20° C)
Vapour density	: 3,46
Density [g/cm³]	: 0.8
Relative density, gas (air=1)	: 3.5
Relative density, liquid (water=1)	: N/A
Solubility in water [% weight]	: 2 (20° C)

MATERIAL SAFETY DATA SHEET (MSDS)
iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
9. Physical and chemical properties (continued)

Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: N/A
Viscosity at 40°C [mm ² /s]	: N/A

9.2. Other information

Explosive properties	: N/A
Explosion limits - upper [%]	: 8
Explosion limits - lower [%]	: 1.2
Oxidising properties	: No data available.

10. Stability and reactivity
10.1. Reactivity

Reactivity	: Not established.
------------	--------------------

10.2. Chemical stability

Chemical stability	: Stable under recommended storage conditions.
--------------------	--

10.3. Possibility of hazardous reactions

Hazardous reactions	: Not established.
---------------------	--------------------

10.4. Conditions to avoid

Conditions to avoid	: Direct sunlight. Extremely high or low temperatures. Open flame.
---------------------	--

10.5. Incompatible materials

Materials to avoid	: Strong acids. Strong bases.
--------------------	-------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	: Fumes. Carbon monoxide. Carbon dioxide. May release flammable gases.
----------------------------------	---

11. Toxicological information
11.1. Information on toxicological effects

MATERIAL SAFETY DATA SHEET (MSDS)
iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
11. Toxicological information (continued)
Acute toxicity

- Inhalation : Harmful if inhaled.
- Dermal : Based on available data, the classification criteria are not met.
- Ingestion : Based on available data, the classification criteria are not met.

Corrosion

: Based on available data, the classification criteria are not met.

Irritation

 : Causes serious eye irritation.
 May cause respiratory irritation.
 Repeated exposure may cause skin dryness or cracking.

Sensitization

: Based on available data, the classification criteria are not met.

Mutagenicity

: Based on available data, the classification criteria are not met.

Carcinogenicity

: Based on available data, the classification criteria are not met.

Toxic for reproduction

: Based on available data, the classification criteria are not met.

STOT-single exposure

: Based on available data, the classification criteria are not met.

STOT-repeated exposure

: Based on available data, the classification criteria are not met.

Aspiration hazard

: Based on available data, the classification criteria are not met.

12. Ecological information
12.1. Toxicity.
Toxicity information : Not established.

12.2. Persistence - degradability.
Persistence - degradability : Biodegradable.

12.3. Bioaccumulative potential
Bioaccumulative potential : Not established.

12.4. Mobility in soil
Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment
Results of PBT and vPvB assessment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects
Environmental precautions : Avoid release to the environment.

MATERIAL SAFETY DATA SHEET (MSDS)
iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
13. Disposal considerations
13.1. Waste treatment methods

General	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Special precautions	: Handle empty containers with care because residual vapours are flammable.

14. Transport information
14.1. Land transport (ADR-RID)

Proper shipping name	: METHYL ISOBUTYL KETONE
UN N°	: 1245
H.I. nr	: 33
ADR - Class	: 3
Labelling - Transport	: 3 : Flammable liquid.



ADR - Classification code	: F1
ADR - Group	: II
ADR - Packing instructions	: P001 R001
ADR - Limited Quantity	: 1 L
ADR - Tunnel code	



: D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG). [English only]

Proper shipping name	: METHYL ISOBUTYL KETONE
UN N°	: 1245
IMO-IMDG - Class or division	: 3 : Flammable liquid.
IMO-IMDG - Packing group	: II
IMO-IMDG - Packing instructions	: P001
IMO-IMDG - Limited quantities	: 1 L

MATERIAL SAFETY DATA SHEET (MSDS)
iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)
14. Transport information (continued)

IMO-IMDG - Marine pollution : No
 EMS-Nr : F-E S-D

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name : METHYL ISOBUTYL KETONE
 UN N° : 1245
 IATA - Class or division : 3 : Flammable liquid.
 IATA - Packing group : II
 IATA - Passenger and Cargo Aircraft : ALLOWED
 - Passenger and Cargo - Packing : 353
 instruction
 - Passenger and Cargo - Maximum : 5 L
 Quantity/Packing
 IATA - Cargo only : ALLOWED
 - Cargo only - Packing instruction : 364
 - Cargo only - Maximum Quantity/ : 60 L
 Packing
 IATA - Limited Quantities : 1 L
 ERG-Nr : 3L

15. Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental : Ensure all national/local regulations are observed.
 regulations/legislation specific for the
 substance or mixture
 REACH Restrictions - Annex XVII : The components of this product are not subject to restrictions.
 REACH Authorisation - Annex XIV : The components of this product are not subject to authorization.

15.2. Chemical Safety Assessment

Chemical Safety Assessment : It has not been carried out.

16. Other information

Revision : Revision - See : *
 Abbreviations and acronyms : PBT: persistent, bioaccumulative and toxic.
 vPvB: very persistent and very bioaccumulative
 Sources of key data used : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF
 THE COUNCIL of 16 December 2008 on classification, labelling and packaging of
 substances and mixtures, amending and repealing Directives 67/548/EEC and

MATERIAL SAFETY DATA SHEET (MSDS)

iso-BUTYL METHYL KETONE AR (METHYL-iso-BUTYL KETONE)

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document