

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

n-BUTYL ACETATE AR (1-BUTYL ACETATE)

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : n-BUTYL ACETATE AR (1-BUTYL ACETATE)

Product code : SS0110900500

Identification of the product : N-BUTYL ACETATE AR 99.5%
 CAS No :123-83-4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification SUVCHEM
 Chaitanya Tower, 2nd Floor, Office # 206,
 Siddharth Nagar, S.V. Road,
 Goregaon (West), Mumbai - 400062,
 Maharashtra, India.
 Contact: +91 22 28725393 / 94 / 95
 Email ID: info@suvchem.com/care@suvchem.com

1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification : R10
 R66
 R67

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Specific Target Organ Toxicity - Single exposure - Narcotic effects - Category 3 -
 Warning (CLP : STOT SE 3) H336

Physical hazards : Flammable liquids - Category 3 - Warning (CLP : Flam. Liq. 3) H226

2.2. Label elements

Labelling EC 67/548 or EC 1999/45

MATERIAL SAFETY DATA SHEET (MSDS)

n-BUTYL ACETATE AR (1-BUTYL ACETATE)

2. Hazards identification -DSD (continued)

Symbol(s)



Symbol(s)

: F : Highly flammable

R Phrase(s)

: R10 : Flammable.

R66 : Repeated exposure may cause skin dryness or cracking.

R67 : Vapours may cause drowsiness and dizziness.

S Phrase(s)

: S25 : Avoid contact with eyes.

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms



Signal words

: Warning

Hazard statements

: H226 : Flammable liquid and vapour.

H336 : May cause drowsiness or dizziness.

Precautionary statements

• Prevention

: P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment.

P210: Keep away from heat, sparks, open flames or hot surfaces. - No smoking.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P271: Use only outdoors or in a well-ventilated area.

P261: Avoid breathing dust, fume, gas, mist, vapours, spray.

P233: Keep container tightly closed.

• Response

: P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing.

P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378: In case of fire: Use for extinction.

• Storage

: P403+P233: Store in well-ventilated place. Keep container tightly closed.

P403+P235: Store in well-ventilated place. Keep cool.

P405: Store locked up.

• Disposal considerations

: P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Other hazards

: The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

n-BUTYL ACETATE AR (1-BUTYL ACETATE)

3. Composition/information on ingredients

Substance / Preparation : N-BUTYL ACETATE AR 99.5%
 CAS No :123-83-4
 Substance.

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures

4.1. Description of first aid measures

Inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin contact : Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing.

Eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

Ingestion : Obtain emergency medical attention. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use : May cause drowsiness or dizziness.
 Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

Surrounding fires : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory protection.

MATERIAL SAFETY DATA SHEET (MSDS)

n-BUTYL ACETATE AR (1-BUTYL ACETATE)

5. Fire-fighting measures (continued)

Special procedures : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection.
 Ventilate area.
 Avoid breathing dust, fume, gas, mist, vapours, spray.

Technical measures : Use special care to avoid static electric charges.

Special precautions : Remove ignition sources. No naked lights. No smoking.

For non-emergency personnel : Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling

Handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.
 Handle empty containers with care because residual vapours are flammable. Take precautionary measures against static discharge.
 Use only outdoors or in a well-ventilated area.

Technical protective measures : Provide good ventilation in process area to prevent formation of vapour.
 Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. Use explosion-proof electrical, ventilating, lighting, ..., equipment.

Special precautions : No naked lights. No smoking.
 Avoid breathing dust, fume, gas, mist, vapours, spray.

MATERIAL SAFETY DATA SHEET (MSDS)

n-BUTYL ACETATE AR (1-BUTYL ACETATE)

7. Handling and storage (continued)

7.2. Conditions for safe storage, including any incompatibilities

Storage	: Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Ground/bond container and receiving equipment. Keep container tightly closed.
Storage - away from	: Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Specific end use(s)	: None.
---------------------	---------

8. Exposure controls/personal protection

8.1. Exposure controls

Personal protection	: Avoid all unnecessary exposure.
• Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
• Hand protection	: Wear protective gloves.
• Eye protection	: Chemical goggles or safety glasses.
• Others	: When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits	: No data available.
------------------------------	----------------------

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state at 20 °C	: Liquid.
Colour	: Clear Colorless
Odour	: Mild, fruity odor
Odour threshold	: No data available.
pH value	: No data available.
Melting point [°C]	: -78 °C
Decomposition point [°C]	: N/A
Critical temperature [°C]	: N/A
Auto-ignition temperature [°C]	: N/A
Flammability (solid, gas)	: Flammable. Flammable liquid and vapour.

MATERIAL SAFETY DATA SHEET (MSDS)
n-BUTYL ACETATE AR (1-BUTYL ACETATE)
9. Physical and chemical properties (continued)

Flash point [°C]	: 23 °C
Boiling point [°C]	: 124 - 126 °C
Initial boiling point [°C]	: 124 °C
Final boiling point [°C]	: 126 °C
Evaporation rate	: 1
Vapour pressure [20°C]	: 15 @ 25C
Vapour pressure mm/Hg	: N/A
Vapour density	: 4,01
Density [g/cm3]	: 0,8822
Relative density, gas (air=1)	: 0,88
Relative density, liquid (water=1)	: N/A
Solubility in water [% weight]	: 0.7% @ 20C
Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: N/A
Viscosity at 40°C [mm2/s]	: N/A

9.2. Other information

Explosive properties	: N/A
Explosion limits - upper [%]	: 7,60%
Explosion limits - lower [%]	: 1,70%
Oxidising properties	: No data available.

10. Stability and reactivity
10.1. Reactivity

Reactivity	: Not established.
------------	--------------------

10.2. Chemical stability

Chemical stability	: Stable under recommended storage conditions.
--------------------	--

10.3. Possibility of hazardous reactions

Hazardous reactions	: Not established.
---------------------	--------------------

10.4. Conditions to avoid

Conditions to avoid	: Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.
---------------------	--

MATERIAL SAFETY DATA SHEET (MSDS)

n-BUTYL ACETATE AR (1-BUTYL ACETATE)

10. Stability and reactivity (continued)

10.5. Incompatible materials

Materials to avoid : Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products : Fumes. Carbon monoxide. Carbon dioxide.
May release flammable gases.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity

- Inhalation : Based on available data, the classification criteria are not met.
- Dermal : Based on available data, the classification criteria are not met.
- Ingestion : Based on available data, the classification criteria are not met.

Corrosion

: Based on available data, the classification criteria are not met.

Irritation

: Repeated exposure may cause skin dryness or cracking.

Sensitization

: Based on available data, the classification criteria are not met.

Mutagenicity

: Based on available data, the classification criteria are not met.

Carcinogenicity

: Based on available data, the classification criteria are not met.

Toxic for reproduction

: Based on available data, the classification criteria are not met.

STOT-single exposure

: May cause drowsiness or dizziness.

STOT-repeated exposure

: Based on available data, the classification criteria are not met.

Aspiration hazard

: Based on available data, the classification criteria are not met.

12. Ecological information

12.1. Toxicity

Toxicity information : Not established.

12.2. Persistence - degradability

Persistence - degradability : Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential : Not established.

MATERIAL SAFETY DATA SHEET (MSDS)

n-BUTYL ACETATE AR (1-BUTYL ACETATE)

12. Ecological information (continued)

12.4. Mobility in soil

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions : Avoid release to the environment.

13. Disposal considerations

13.1. Waste treatment methods

General : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
 Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Special precautions : Handle empty containers with care because residual vapours are flammable.

14. Transport information

14.1. Land transport (ADR-RID)

Proper shipping name : BUTYL ACETATES
 UN N° : 1123
 H.I. nr : 30
 ADR - Class : 3
 Labelling - Transport : 3 : Flammable liquid.



ADR - Classification code : F1
 ADR - Group : III
 ADR - Packing instructions : P001 R001 LP001
 ADR - Limited Quantity : 5 L

MATERIAL SAFETY DATA SHEET (MSDS)

n-BUTYL ACETATE AR (1-BUTYL ACETATE)

14. Transport information (continued)

ADR - Tunnel code : D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.



14.2. Sea transport (IMDG) [English only]

Proper shipping name : BUTYL ACETATES
UN N° : 1123
IMO-IMDG - Class or division : 3 : Flammable liquid.
IMO-IMDG - Packing group : III
IMO- IMDG - Packing instructions : P001 LP01
IMO-IMDG - Limited quantities : 5 L
IMO-IMDG - Marine pollution : No
EMS-Nr : F-E S-D

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name : BUTYL ACETATES
UN N° : 1123
IATA - Class or division : 3 : Flammable liquid.
IATA - Packing group : III
IATA - Passenger and Cargo Aircraft : ALLOWED
 - Passenger and Cargo - Packing : 355
instruction
 - Passenger and Cargo - Maximum : 60 L
Quantity/Packing
IATA - Cargo only : ALLOWED
 - Cargo only - Packing instruction : 366
 - Cargo only - Maximum Quantity/ : 220 L
Packing
IATA - Limited Quantities : 10 L
ERG-Nr : 3L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental regulations/legislation specific for the substance or mixture : Ensure all national/local regulations are observed.

MATERIAL SAFETY DATA SHEET (MSDS)
n-BUTYL ACETATE AR (1-BUTYL ACETATE)

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document