

#### CHAITANYA CH5, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

### MATERIAL SAFETY DATA SHEET (MSDS)

## **DI-ISO-PROPYL ETHER AR**

#### 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
Trade name	: DI-ISO-PROPYL ETHER AR	
Product code	: SS0116400500	
Identification of the product	: DI-ISO-PROPYL ETHER AR 98.5% CAS No :108-20-3	
1.2. Relevant identified uses of the substance or mixture and uses advised against		
Use	: Industrial. For professional use only.	
1.3. Details of the supplier of the safety data sheet		
Company identification	SUVCHEM Chaitanya Tower, 2nd Floor, Office # 206, Siddharth Nagar, S.V. Road, Goregaon (West), Mumbai - 400062, Maharashtra, India.	
	Contact: +91 22 28725393 / 94 / 95	
1.4. Emergency telephone number	Email ID: info@suvchem.com/care@suvchem.com	
Phone no.	: + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [ Office hours ]	

#### 2. Hazards identification -DSD

#### 2.1. Classification of the substance or mixture

#### Classification EC 67/548 or EC 1999/45

Classification	: F; R11
	R19
	R66
	R67

#### Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards	: Specific Target Organ Toxicity - Single exposure - Narcotic effects - Category 3 - Warning (CLP : STOT SE 3) H336
Physical hazards	: Flammable liquids - Category 2 - Danger (CLP : Flam. Liq. 2) H225

2.2. Label elements

Labelling EC 67/548 or EC 1999/45



#### CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

# **DI-ISO-PROPYL ETHER AR**

Hazards identification -DSD	
Symbol(s)	<b>*</b>
Symbol(s)	: F : Highly flammable
R Phrase(s)	: R11 : Highly flammable. R19 : May form explosive peroxides. R66 : Repeated exposure may cause skin dryness or cracking. R67 : Vapours may cause drowsiness and dizziness.
S Phrase(s)	: S16 : Keep away from sources of ignition - No smoking. S29 : Do not empty into drains. S33 : Take precautionary measures against static discharges.
Labelling Regulation EC 1272/2	<u>008 (CLP)</u>
Hazard pictograms	
Signal words	: Danger
Hazard statements	<ul> <li>H225 : Highly flammable liquid and vapour.</li> <li>H336 : May cause drowsiness or dizziness.</li> </ul>
Precautionary statements	
Prevention	<ul> <li>P240: Ground/bond container and receiving equipment.</li> <li>P241: Use explosion-proof electrical, ventilating, lighting,, equipment.</li> <li>P210: Keep away from heat, sparks, open flames or hot surfaces No smoking</li> <li>P280: Wear protective gloves, protective clothing, eye protection, face protection</li> <li>P271: Use only outdoors or in a well-ventilated area.</li> <li>P261: Avoid breathing dust, fume, gas, mist, vapours, spray.</li> <li>P233: Keep container tightly closed.</li> </ul>
• Response	<ul> <li>P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing.</li> <li>P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminate clothing. Rinse skin with water/shower.</li> <li>P370+P378: In case of fire: Use for extinction.</li> </ul>
• Storage	<ul> <li>P403+P233: Store in well-ventilated place. Keep container tightly closed.</li> <li>P403+P235: Store in well-ventilated place. Keep cool.</li> <li>P405: Store locked up.</li> </ul>
<ul> <li>Disposal considerations</li> </ul>	: P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international



# MATERIAL SAFETY DATA SHEET (MSDS)

# **DI-ISO-PROPYL ETHER AR**

#### 2. Hazards identification -DSD (continued)

Other hazards

: The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

#### 3. Composition/information on ingredients

Substance / Preparation

: DI-ISO-PROPYL ETHER AR 98.5% CAS No :108-20-3 Substance.

Contains no other components or impurities which will influence the classification of the product.

#### 4. First aid measures

# 4.1. Description of first aid measures

Inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.	
Skin contact	: Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.	
Eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.	
Ingestion	: Obtain emergency medical attention. Rinse mouth. Do NOT induce vomiting.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms relating to use	: May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.	
4.3. Indication of any immediate medical attention and special treatment needed		
General information	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).	

#### 5. Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.	
Unsuitable extinguishing media	: Do not use a heavy water stream.	
Surrounding fires	: Use water spray or fog for cooling exposed containers.	

5.2. Special hazards arising from the substance or mixture



#### CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

## **DI-ISO-PROPYL ETHER AR**

. Fire-fighting measures (continued)		
Flammable class	: Highly flammable liquid and vapour. May form explosive peroxides.	
Hazardous combustion products	: Under fire conditions, hazardous fumes will be present. May form flammable/ explosive vapour-air mixture.	
5.3. Advice for fire-fighters		
Protection against fire	: Do not enter fire area without proper protective equipment, including respiratory protection.	
Special procedures	: Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water enter environment. Evacuate area. DO NOT fight fire when fire reaches explosive	

#### 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures		
For emergency responders	: Equip cleanup crew with proper protection. Ventilate area. Avoid breathing dust, fume, gas, mist, vapours, spray.	
Technical measures	: Use special care to avoid static electric charges.	
Special precautions	: Remove ignition sources. No naked lights. No smoking. Reacts vigorously with strong oxidizers and acids.	
For non-emergency personnel	: Evacuate unnecessary personnel.	
6.2. Environmental precautions		
Environmental precautions	: Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.	
6.3. Methods and material for containment and cleaning up		
Clean up methods	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Store away from other materials. Collect spillage.	
6.4. Reference to other sections		

See section 8. Exposure controls/personal protection

#### 7. Handling and storage

#### 7.1. Precautions for safe handling

Handling

: Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Handle empty containers with care because residual vapours are flammable.



#### CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

# **DI-ISO-PROPYL ETHER AR**

7. Handling and storage (continue	∋d)
	Use only outdoors or in a well-ventilated area.
Technical protective measures	Provide good ventilation in process area to prevent formation of vapour. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating, lighting,, equipment.
Special precautions	: No naked lights. No smoking. Avoid breathing dust, fume, gas, mist, vapours, spray.
7.2. Conditions for safe storage, in	<u>cluding any incompatibilities</u>
Storage	: Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Keep container tightly closed. Ground/bond container and receiving equipment.
Storage - away from	: Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources. Oxidizing agent.
<u>7.3. Specific end use(s)</u>	
Specific end use(s)	: None.
8. Exposure controls/personal pro	otection
8.1. Exposure controls	

Personal protection	: Avoid all unnecessary exposure.	
<ul> <li>Respiratory protection</li> </ul>	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.	
<ul> <li>Hand protection</li> </ul>	: Wear protective gloves.	
<ul> <li>Eye protection</li> </ul>	: Chemical goggles or safety glasses.	
• Others	: When using, do not eat, drink or smoke.	
8.2. Control parameters		
Occupational Exposure Limits	: No data available.	

#### 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state at 20 °C	: Liquid.
Colour	: Clear Colorless
Odour	: Etheral odour
Odour threshold	: No data available.



# MATERIAL SAFETY DATA SHEET (MSDS)

# **DI-ISO-PROPYL ETHER AR**

#### 9. Physical and chemical properties (continued)

pH value	: No data available.
Melting point [°C]	: -85 °C
Decomposition point [°C]	: N/A
Critical temperature [°C]	: N/A
Auto-ignition temperature [°C]	: 4430C
Flammability (solid, gas)	: Highly flammable liquid and vapour. Flammable.
Flash point [°C]	: -29 °C
Boiling point [°C]	: 65 - 70 °C
Initial boiling point [°C]	: 65°C
Final boiling point [°C]	: 70 °C
Evaporation rate	: 8
Vapour pressure [20°C]	: N/A
Vapour pressure mm/Hg	: 119 @ 20C
Vapour density	: 3,5
Density [g/cm3]	: 0,78
Relative density, gas (air=1)	: N/A
Relative density, liquid (water=1)	
Solubility in water [% weight]	: 0.2g/100g water @ 20
Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: N/A
Viscosity at 40°C [mm2/s]	: N/A
9.2. Other information	
Explosive properties	: May form explosive peroxides. N/A
Explosion limits - upper [%]	: 21%
Explosion limits - lower [%]	: 1%
Oxidising properties	: No data available.

#### 10. Stability and reactivity

10.1. Reactivity	
Reactivity	: Not established.

10.2. Chemical stability



#### CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

# **DI-ISO-PROPYL ETHER AR**

10. Stability and reactivity (continued)		
Chemical stability	: Stable under recommended storage conditions.	
10.3. Possibility of hazardous reactions		
Hazardous reactions	: Not established.	
10.4. Conditions to avoid		
Conditions to avoid	: Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks. Open flame. Direct sunlight. Overheating.	
10.5. Incompatible materials		
Materials to avoid	: Strong acids. Strong bases. Oxidizing agent.	
10.6. Hazardous decomposition products		
Hazardous decomposition products	: Fumes. Carbon monoxide. Carbon dioxide. May release flammable gases.	

#### 11. Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	
Inhalation	: Based on available data, the classification criteria are not met.
• Dermal	: Based on available data, the classification criteria are not met.
Ingestion	: Based on available data, the classification criteria are not met.
Corrosion	: Based on available data, the classification criteria are not met.
Irritation	: Repeated exposure may cause skin dryness or cracking.
Sensitization	: Based on available data, the classification criteria are not met.
Mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Toxic for reproduction	: Based on available data, the classification criteria are not met.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Based on available data, the classification criteria are not met.
Aspiration hazard	: Based on available data, the classification criteria are not met.

#### 12. Ecological information

12.1. Toxicity



# MATERIAL SAFETY DATA SHEET (MSDS)

# **DI-ISO-PROPYL ETHER AR**

12. Ecological information (continu	Jed)
Toxicity information	: Not established.
<u>12.2. Persistence - degradability</u>	
Persistence - degradability	: Biodegradable.
12.3. Bioaccumulative potential	
Bioaccumulative potential	: Not established.
<u>12.4. Mobility in soil</u>	
Mobility in soil	: Not established.
12.5. Results of PBT and vPvB asse	essment
Results of PBT and vPvB assessme	ent : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.
12.6. Other adverse effects	
Environmental precautions	: Avoid release to the environment.
13. Disposal considerations	
13.1. Waste treatment methods	
General	<ul> <li>Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.</li> <li>Hazardous waste due to potential risk of explosion.</li> <li>Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</li> </ul>
Special precautions	: Handle empty containers with care because residual vapours are flammable.
14. Transport information	
14.1. Land transport (ADR-RID)	
Proper shipping name	: DIISOPROPYL ETHER

. DIISOPROPILEINER
: 1159
: 33
: 3
: 3 : Flammable liquid.



#### CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

# MATERIAL SAFETY DATA SHEET (MSDS)

# **DI-ISO-PROPYL ETHER AR**

#### 14. Transport information (continued)



- ADR Classification code
- ADR Group
- ADR Packing instructions
- ADR Limited Quantity
- ADR Tunnel code
- : P001 R001
- :1L

: F1

: 11

: D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.



#### 14.2. Sea transport (IMDG) [English only]

: DIISOPROPYL ETHER
: 1159
: 3 : Flammable liquid.
: 11
: P001
: 1 L
: No
: F-E S-D

#### 14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name UN N°	: DIISOPROPYL ETHER : 1159
IATA - Class or division	: 3 : Flammable liquid.
IATA - Packing group	: 11
IATA - Passenger and Cargo Aircraft	: ALLOWED
- Passenger and Cargo - Packing instruction	: 353
- Passenger and Cargo - Maximum Quantity/Packing	: 5 L
IATA - Cargo only	: ALLOWED
- Cargo only - Packing instruction	: 364
- Cargo only - Maximum Quantity/ Packing	: 60 L



# MATERIAL SAFETY DATA SHEET (MSDS)

# **DI-ISO-PROPYL ETHER AR**

In accordance with REACH Regulation (CE) Nº 1907/2006 and with CLP Regulation (CE) Nº 1272/2008

# DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its
  comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of
  the material by a properly trained person using this product.

End of document

Page :10

AN ISO 9001: 2015 CERTIFIED