

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

O-XYLENE (FOR SYNTHESIS)

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : O-XYLENE (FOR SYNTHESIS)

Product code : SS0120102500

Identification of the product : O-XYLENE 99%
 CAS No: 95-47-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification SUVCHEM
 Chaitanya Tower, 2nd Floor, Office # 206,
 Siddharth Nagar, S.V. Road,
 Goregaon (West), Mumbai - 400062,
 Maharashtra, India.
 Contact: +91 22 28725393 / 94 / 95
 Email ID: info@suvchem.com/care@suvchem.com

1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification : R10
 Xn; R20/21
 Xi; R38

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Acute toxicity, Inhalation - Category 4 - Warning (CLP : Acute Tox. 4) H332
 Skin irritation - Category 2 - Warning (CLP : Skin Corr. 2) H315
 Acute toxicity, dermal - Category 4 - Warning (CLP : Acute Tox. 4) H312

Physical hazards : Flammable liquids - Category 3 - Warning (CLP : Flam. Liq. 3) H226

2.2. Label elements

Labelling EC 67/548 or EC 1999/45

MATERIAL SAFETY DATA SHEET (MSDS)
O-XYLENE (FOR SYNTHESIS)
2. Hazards identification -DSD (continued)

Symbol(s)



Symbol(s)

: Xn : Harmful

R Phrase(s)

: R10 : Flammable.

R20/21 : Harmful by inhalation and in contact with skin.

R38 : Irritating to skin.

S Phrase(s)

: S25 : Avoid contact with eyes.

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms



Signal words

: Warning

Hazard statements

: H226 : Flammable liquid and vapour.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H332 : Harmful if inhaled.

Precautionary statements

• Prevention

: P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment.

P210: Keep away from heat, sparks, open flames or hot surfaces. - No smoking.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P271: Use only outdoors or in a well-ventilated area.

P261: Avoid breathing dust, fume, gas, mist, vapours, spray.

P233: Keep container tightly closed.

P264: Wash thoroughly after handling.

• Response

: P302+P352: IF ON SKIN : Wash with plenty of soap and water.

P332+P313: If skin irritation occurs : Get medical advice.

P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing.

P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse.

P370+P378: In case of fire: Use for extinction.

• Storage

: P403+P235: Store in well-ventilated place. Keep cool.

• Disposal considerations

: P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

MATERIAL SAFETY DATA SHEET (MSDS)
O-XYLENE (FOR SYNTHESIS)
2. Hazards identification -DSD (continued)

Other hazards : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

Substance / Preparation : O-XYLENE 99%

Substance.

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures
4.1. Description of first aid measures

Inhalation : Assure fresh air breathing. Allow the victim to rest. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin contact : Immediately call a POISON CENTER or doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. Get medical advice. Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. If skin irritation occurs :

Eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

Ingestion : Obtain emergency medical attention. Do NOT induce vomiting. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use : Repeated exposure to this material can result in absorption through skin causing significant health hazard.
Causes skin irritation.
Danger of serious damage to health by prolonged exposure through inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures
5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

MATERIAL SAFETY DATA SHEET (MSDS)
O-XYLENE (FOR SYNTHESIS)
5. Fire-fighting measures (continued)

Surrounding fires : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Special procedures : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

6. Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection.
Ventilate area.

Technical measures : Use special care to avoid static electric charges.

Special precautions : Remove ignition sources. No naked lights. No smoking.

For non-emergency personnel : Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage
7.1. Precautions for safe handling

Handling : Handle empty containers with care because residual vapours are flammable. Wash thoroughly after handling. Avoid breathing dust, fume, gas, mist, vapours, spray. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.

MATERIAL SAFETY DATA SHEET (MSDS)
O-XYLENE (FOR SYNTHESIS)
7. Handling and storage (continued)

- Technical protective measures** : Provide good ventilation in process area to prevent formation of vapour. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating, lighting, ..., equipment. Use only non-sparking tools.
- Special precautions** : No naked lights. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Storage** : Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Ground/bond container and receiving equipment. Keep container tightly closed.
- Storage - away from** : Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

- Specific end use(s)** : None.

8. Exposure controls/personal protection
8.1. Exposure controls

- Personal protection** : Avoid all unnecessary exposure.
- **Respiratory protection** : In case of insufficient ventilation, wear suitable respiratory equipment.
 - **Hand protection** : Wear protective gloves.
 - **Skin protection** : Wear suitable protective clothing.
 - **Eye protection** : Chemical goggles or safety glasses.
 - **Others** : When using, do not eat, drink or smoke.

8.2. Control parameters

- Occupational Exposure Limits** : No data available.

9. Physical and chemical properties
9.1. Information on basic physical and chemical properties

- Physical state at 20 °C** : Liquid.
- Colour** : Clear Colorless
- Odour** : Characteristic odour
- Odour threshold** : No data available.
- pH value** : No data available.
- Melting point [°C]** : No data available.

MATERIAL SAFETY DATA SHEET (MSDS)
O-XYLENE (FOR SYNTHESIS)
9. Physical and chemical properties (continued)

| | |
|------------------------------------|--|
| Decomposition point [°C] | : N/A |
| Critical temperature [°C] | : N/A |
| Auto-ignition temperature [°C] | : 464 °C |
| Flammability (solid, gas) | : Flammable. Flammable liquid and vapour. |
| Flash point [°C] | : 31 °C |
| Boiling point [°C] | : 143 - 145 °C |
| Initial boiling point [°C] | : 143 °C |
| Final boiling point [°C] | : 145 °C |
| Evaporation rate | : 1 |
| Vapour pressure [20°C] | : 7 mm Hg @ 20 °C |
| Vapour pressure mm/Hg | : 7 mm Hg @ 20C |
| Vapour density | : 3,7 |
| Density [g/cm3] | : 0,88 |
| Relative density, gas (air=1) | : N/A |
| Relative density, liquid (water=1) | : N/A |
| Solubility in water [% weight] | : Insoluble. |
| Solubility in water | : N/A |
| Log Pow octanol / water at 20°C | : No data available. |
| Solubility | : N/A |
| Viscosity at 40°C [mm2/s] | : N/A |

9.2. Other information

| | |
|------------------------------|----------------------|
| Explosive properties | : N/A |
| Explosion limits - upper [%] | : 6,70% |
| Explosion limits - lower [%] | : 0,90% |
| Oxidising properties | : No data available. |

10. Stability and reactivity
10.1. Reactivity

| | |
|------------|--------------------|
| Reactivity | : Not established. |
|------------|--------------------|

10.2. Chemical stability

| | |
|--------------------|--|
| Chemical stability | : Stable under recommended storage conditions. |
|--------------------|--|

10.3. Possibility of hazardous reactions

MATERIAL SAFETY DATA SHEET (MSDS)
O-XYLENE (FOR SYNTHESIS)
10. Stability and reactivity (continued)

Hazardous reactions : Not established.

10.4. Conditions to avoid

Conditions to avoid : Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Materials to avoid : Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products : Fumes. Carbon monoxide. Carbon dioxide. May release flammable gases.

11. Toxicological information
11.1. Information on toxicological effects
Acute toxicity

- **Inhalation** : Harmful if inhaled.
- **Dermal** : Harmful in contact with skin.
- **Ingestion** : Based on available data, the classification criteria are not met.

Corrosion : Based on available data, the classification criteria are not met.

Irritation : Causes skin irritation.

Sensitization : Based on available data, the classification criteria are not met.

Mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Toxic for reproduction : Based on available data, the classification criteria are not met.

STOT-single exposure : Based on available data, the classification criteria are not met.

STOT-repeated exposure : Based on available data, the classification criteria are not met.

Aspiration hazard : Based on available data, the classification criteria are not met.

12. Ecological information
12.1. Toxicity

Toxicity information : Not established.

12.2. Persistence - degradability

MATERIAL SAFETY DATA SHEET (MSDS)
O-XYLENE (FOR SYNTHESIS)
12. Ecological information (continued)

Persistence - degradability : Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential : Not established.

12.4. Mobility in soil

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions : Avoid release to the environment.

13. Disposal considerations
13.1. Waste treatment methods

General : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
 Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Special precautions : Handle empty containers with care because residual vapours are flammable.

14. Transport information
14.1. Land transport (ADR-RID)

Proper shipping name : XYLENES
 UN N° : 1307
 H.I. nr : 30
 ADR - Class : 3
 Labelling - Transport : 3 : Flammable liquid.



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.
 CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

O-XYLENE (FOR SYNTHESIS)

14. Transport information (continued)

ADR - Classification code : F1
 ADR - Group : III
 ADR - Packing instructions : P001 R001 LP001
 ADR - Limited Quantity : 5 L
 ADR - Tunnel code



: D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name : XYLENES
 UN N° : 1307
 IMO-IMDG - Class or division : 3 : Flammable liquid.
 IMO-IMDG - Packing group : III
 IMO-IMDG - Packing instructions : P001 LP01
 IMO-IMDG - Limited quantities : 5 L
 IMO-IMDG - Marine pollution : No
 EMS-Nr : F-E S-D

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name : XYLENES
 UN N° : 1307
 IATA - Class or division : 3 : Flammable liquid.
 IATA - Packing group : III
 IATA - Passenger and Cargo Aircraft : ALLOWED
 - Passenger and Cargo - Packing instruction : 355
 - Passenger and Cargo - Maximum Quantity/Packing : 60 L
 IATA - Cargo only : ALLOWED
 - Cargo only - Packing instruction : 366
 - Cargo only - Maximum Quantity/Packing : 220 L
 IATA - Limited Quantities : 10 L
 ERG-Nr : 3L

MATERIAL SAFETY DATA SHEET (MSDS)

O-XYLENE (FOR SYNTHESIS)

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document