

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### ZINC OXIDE LR

#### 1. Product Identification

**Synonyms:** Chinese white; zinc white; flowers of zinc; calamine  
**CAS No.:** 1314-13-2

Product Coad: Z0220005000

**Molecular Weight:** 81.38  
**Chemical Formula:** ZnO

#### 2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Zinc Oxide	1314-13-2	99 - 100%	Yes

#### 3. Hazards Identification

##### Emergency Overview CAUTION! MAY IRRITATE RESPIRATORY TRACT.

**Inhalation:** May cause irritation to the respiratory tract. Symptoms may include coughing and shortness of breath. Inhalation can cause a flu-like illness (metal fume fever). This 24- to 48-hour illness is characterized by chills, fever, aching muscles, dryness in the mouth and throat and headache.

**Ingestion:** Large oral doses may cause irritation to the gastrointestinal tract.

**Skin Contact:** Not expected to be a health hazard from skin exposure.

**Eye Contact:** Not expected to be a health hazard.

**Chronic Exposure:**

#### 4. First Aid Measures

**Inhalation:** Remove to fresh air. Get medical attention for any breathing difficulty.

**Ingestion:** Not expected to require first aid measures. If large amounts were swallowed, give water to drink and get medical advice.

**Skin Contact:** Not expected to require first aid measures. Wash exposed area with soap and water. Get medical advice if irritation develops.

**Eye Contact:** Not expected to require first aid measures. Wash thoroughly with running water. Get medical advice if irritation develops.

#### 5. Fire Fighting Measures

**Fire:** Not considered to be a fire hazard.

**Explosion:** Finely divided powder presents an explosion hazard.

**Fire Extinguishing Media:** Use any means suitable for extinguishing surrounding fire.

**Special Information:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Zinc oxide fume may be released when heated.

#### 6. Accidental Release Measures

Clean-up personnel require protective clothing and respiratory protection from dust. Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal.

#### 7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

#### 8. Exposure Controls/Personal Protection

##### Airborne Exposure Limits:

Zinc oxide:-OSHA Permissible Exposure Limit (PEL):fume: 5 mg/m3 (TWA)

respirable fraction: 5 mg/m3 (TWA)

total dusts: 15 mg/m3 (TWA)

-ACGIH Threshold Limit Value (TLV):2 mg/m3 (TWA), 10 mg/m3 (STEL), Respirable fraction

**Ventilation System:** A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general

CHAITANYA CHS, 2<sup>nd</sup> FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAI 400062, MH, INDIA.  
CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

## MATERIAL SAFETY DATA SHEET (MSDS)

### ZINC OXIDE LR

work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

**Personal Respirators (NIOSH Approved):** If the exposure limit is exceeded, a half-face dust/mist respirator may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece dust/mist respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. **Skin Protection:** Wear protective gloves and clean body-covering clothing. **Eye Protection:** Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

#### 9. Physical and Chemical Properties

**Appearance:** White to yellowish-white amorphous powder.  
**Odor:** Odorless. **Solubility:** Insoluble in water, alcohol; soluble in dilute acids.  
**Specific Gravity:** 5.67 **pH:** No information found. **% Volatiles by volume @ 21C (70F):** 0  
**Boiling Point:** Sublimes. **Melting Point:** 1975C (3587F)

#### 10. Stability and Reactivity

**Stability:** Stable under ordinary conditions of use and storage. Absorbs carbon dioxide from air.  
**Hazardous Decomposition Products:** When heated to very high temperatures, zinc oxide sublimes to produce toxic fumes. **Hazardous Polymerization:** Will not occur.  
**Incompatibilities:** Has exploded when mixed with chlorinated rubber. Reacts violently with magnesium, linseed oil. Zinc oxide and magnesium can react explosively when heated.  
**Conditions to Avoid:** Heat, incompatibles.

#### 11. Toxicological Information

Investigated as a mutagen, reproductive effector.

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category
Zinc Oxide (1314-13-2)	No	No	None

#### 12. Ecological Information

**Environmental Fate:** No information found.  
**Environmental Toxicity:** No information found.

#### 13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

#### 14. Transport Information

Not regulated.

#### 15. Regulatory Information

NA

#### 16. Other Information

**NFPA Ratings:** Health: 1 Flammability: 0 Reactivity: 0  
**Label Hazard Warning:** CAUTION! MAY IRRITATE RESPIRATORY TRACT.  
**Label Precautions:** Avoid breathing dust.  
Keep container closed. Use with adequate ventilation.  
**Label First Aid:** If inhaled, remove to fresh air. Get medical attention for any breathing difficulty.  
**Product Use:** Laboratory Reagent.

**MATERIAL SAFETY DATA SHEET (MSDS)**

**ZINC OXIDE LR**

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- **SUVCHEM** Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

**End of document**